


**Mitutoyo**
**Internal micrometer Holtest, Measuring range: 30-40 mm**

**Order data**

Order number	429000 30-40
GTIN	4946368517711
Item class	44A

**Description**
**Version:**

Stainless, all reading parts glare-free satin chrome-plated. Barrel with jet black scale and ratchet. For through holes, measuring faces of hardened steel.

**Optional extras:**

Extensions No. 429010. Setting rings No. 484030.

Calibration: B6

Scale divisions: 0.005 mm

Error limit: 0.006 mm

Barrel Ø: 23 mm

Dimension a: 3.4 mm

Standard measuring depth: 98 mm

Overall length: 140 mm

**Technical description**

Measuring depth with extension	248 mm
Barrel Ø	23 mm
Dimension a	3.4 mm
Standard measuring depth	98 mm
Overall length	140 mm
Measuring range	30 - 40 mm
Error limit	0.006 mm

Scale divisions	0.005 mm
Standard	Manufacturer's standard
Micrometer barrel graduations	1/50 mm
Measurement technology	analogue
Packaging	sturdy box
Calibration	B6
Type of product	3-point internal micrometer

### Services

Calibration 3-point inside micrometer maximum measuring range 50 mm	012900 50
Labelling laser-etched Type	018940
DAkkS calibration 3-point internal micrometer maximum measuring range 200 mm	012910 200
DAkkS calibration 3-point internal micrometer maximum measuring range 200 mm	022510 200
Calibration 3-point inside micrometer maximum measuring range 50 mm	022500 50

### Accessories

Setting ring DIN 2250 C Nominal size Ø 38 mm	484030 38
Setting ring DIN 2250 C Nominal size Ø 30 mm	484030 30
Setting ring DIN 2250 C Nominal size Ø 35 mm	484030 35
Setting ring DIN 2250 C Nominal size Ø 36 mm	484030 36
Extension for internal micrometer Type 3/150	429010 3/150
Setting ring DIN 2250 C Nominal size Ø 34 mm	484030 34
Setting ring DIN 2250 C Nominal size Ø 40 mm	484030 40
Setting ring DIN 2250 C Nominal size Ø 32 mm	484030 32