


Mitutoyo
Internal micrometer Holtest, Measuring range: 6-8 mm

Order data

Order number	429000 6-8
GTIN	4946368517155
Item class	44A

Description
Version:

Stainless, all reading parts glare-free satin chrome-plated. Barrel with jet black scale and ratchet. For through holes, measuring faces of hardened steel.

Optional extras:

Extensions No. 429010. Setting rings No. 484030.

Calibration: B6

Scale divisions: 0.001 mm

Error limit: 0.004 mm

Barrel Ø: 17 mm

Dimension a: 2 mm

Standard measuring depth: 57 mm

Overall length: 106 mm

Technical description

Measuring depth with extension	157 mm
Barrel Ø	17 mm
Standard measuring depth	57 mm
Measuring range	6 - 8 mm
Dimension a	2 mm
Overall length	106 mm
Error limit	0.004 mm

Scale divisions	0.001 mm
Standard	Manufacturer's standard
Micrometer barrel graduations	1/50 mm
Measurement technology	analogue
Packaging	sturdy box
Calibration	B6
Type of product	3-point internal micrometer

Services

Calibration 3-point inside micrometer maximum measuring range 20 mm	012900 20
Labelling laser-etched Type	018940
DAkkS calibration 3-point internal micrometer maximum measuring range 200 mm	012910 200
Calibration 3-point inside micrometer maximum measuring range 20 mm	022500 20
DAkkS calibration 3-point internal micrometer maximum measuring range 200 mm	022510 200

Accessories

Setting ring DIN 2250 C Nominal size Ø 7 mm	484030 7
Setting ring DIN 2250 C Nominal size Ø 6 mm	484030 6
Extension for internal micrometer Type 1/100	429010 1/100
Setting ring DIN 2250 C Nominal size Ø 8 mm	484030 8