


Mitutoyo
Internal micrometer Holtest, Measuring range: 62-75 mm

Order data

Order number	429000 62-75
GTIN	4946368517742
Item class	44A

Description
Version:

Stainless, all reading parts glare-free satin chrome-plated. Barrel with jet black scale and ratchet. For through holes, measuring faces of hardened steel.

Optional extras:

Extensions No. 429010. Setting rings No. 484030.

Calibration: B6

Scale divisions: 0.005 mm

Error limit: 0.006 mm

Barrel Ø: 23 mm

Dimension a: 3.4 mm

Standard measuring depth: 105 mm

Overall length: 156 mm

Technical description

Standard measuring depth	105 mm
Barrel Ø	23 mm
Dimension a	3.4 mm
Measuring range	62 - 75 mm
Overall length	156 mm
Measuring depth with extension	255 mm
Error limit	0.006 mm

Scale divisions	0.005 mm
Standard	Manufacturer's standard
Micrometer barrel graduations	1/50 mm
Measurement technology	analogue
Packaging	sturdy box
Calibration	B6
Type of product	3-point internal micrometer

Services

Calibration 3-point inside micrometer maximum measuring range 100 mm	012900 100
Labelling laser-etched Type	018940
DAkkS calibration 3-point internal micrometer maximum measuring range 200 mm	012910 200
Calibration 3-point inside micrometer maximum measuring range 100 mm	022500 100
DAkkS calibration 3-point internal micrometer maximum measuring range 200 mm	022510 200

Accessories

Setting ring DIN 2250 C Nominal size Ø 75 mm	484030 75
Setting ring DIN 2250 C Nominal size Ø 65 mm	484030 65
Setting ring DIN 2250 C Nominal size Ø 70 mm	484030 70
Extension for internal micrometer Type 4/150	429010 4/150
Setting ring DIN 2250 C Nominal size Ø 60 mm	484030 60