


Mitutoyo**Internal micrometer Holtest, Measuring range: 87-100 mm****Order data**

Order number	429000 87-100
GTIN	4946368517766
Item class	44A

Description**Version:**

Stainless, all reading parts glare-free satin chrome-plated. Barrel with jet black scale and ratchet. For through holes, measuring faces of hardened steel.

Optional extras:

Extensions No. 429010. Setting rings No. 484030.

Calibration: B6

Scale divisions: 0.005 mm

Error limit: 0.006 mm

Barrel Ø: 23 mm

Dimension a: 3.4 mm

Standard measuring depth: 105 mm

Overall length: 156 mm

Technical description

Measuring range	87 - 100 mm
Dimension a	3.4 mm
Measuring depth with extension	255 mm
Standard measuring depth	105 mm
Barrel Ø	23 mm
Overall length	156 mm
Error limit	0.006 mm

Scale divisions	0.005 mm
Standard	Manufacturer's standard
Micrometer barrel graduations	1/50 mm
Measurement technology	analogue
Packaging	sturdy box
Calibration	B6
Type of product	3-point internal micrometer

Services

Calibration 3-point inside micrometer maximum measuring range 100 mm	012900 100
Labelling laser-etched Type	018940
DAkkS calibration 3-point internal micrometer maximum measuring range 200 mm	012910 200
DAkkS calibration 3-point internal micrometer maximum measuring range 200 mm	022510 200
Calibration 3-point inside micrometer maximum measuring range 100 mm	022500 100

Accessories

Setting ring DIN 2250 C Nominal size Ø 100 mm	484030 100
Extension for internal micrometer Type 4/150	429010 4/150
Setting ring DIN 2250 C Nominal size Ø 90 mm	484030 90
Setting ring DIN 2250 C Nominal size Ø 95 mm	484030 95