

Mitutoyo
Internal micrometer Holtest for measuring blind holes, Measuring range: 87-100 mm


Order data

| | |
|--------------|---------------|
| Order number | 429005 87-100 |
| GTIN | 4946368517278 |
| Item class | 44A |

Description

Version:

Stainless, all reading parts glare-free satin chrome-plated. Barrel with jet black scale and ratchet. Blind hole version. **Measuring faces of hardened steel with titanium coating for long tool life.**

Optional extras:

Extensions No. 429010. Setting rings No. 484030.

Calibration: B6

Scale divisions: 0.005 mm

Error limit: 0.006 mm

Barrel Ø: 23 mm

Dimension a: 0.3 mm

Standard measuring depth: 105 mm

Overall length: 156 mm

Technical description

| | |
|--------------------------------|-------------|
| Measuring depth with extension | 255 mm |
| Barrel Ø | 23 mm |
| Standard measuring depth | 105 mm |
| Overall length | 156 mm |
| Dimension a | 0.3 mm |
| Measuring range | 87 - 100 mm |

| | |
|-------------------------------|-----------------------------|
| Error limit | 0.006 mm |
| Scale divisions | 0.005 mm |
| Standard | Manufacturer's standard |
| Micrometer barrel graduations | 1/50 mm |
| Measurement technology | analogue |
| Packaging | sturdy box |
| Calibration | B6 |
| Type of product | 3-point internal micrometer |

Services

| | |
|--|------------|
| Calibration 3-point inside micrometer maximum measuring range 100 mm | 012900 100 |
| Labelling laser-etched Type | 018940 |
| DAkkS calibration 3-point internal micrometer maximum measuring range 200 mm | 012910 200 |
| Calibration 3-point inside micrometer maximum measuring range 100 mm | 022500 100 |
| DAkkS calibration 3-point internal micrometer maximum measuring range 200 mm | 022510 200 |

Accessories

| | |
|---|--------------|
| Setting ring DIN 2250 C Nominal size Ø 100 mm | 484030 100 |
| Setting ring DIN 2250 C Nominal size Ø 90 mm | 484030 90 |
| Extension for internal micrometer Type 4/150 | 429010 4/150 |
| Setting ring DIN 2250 C Nominal size Ø 95 mm | 484030 95 |