

**Mitutoyo****Internal micrometer set, Measuring range: 20-50 mm****Order data**

Order number	429050 20-50
GTIN	4946368518046
Item class	44A

**Description****Version:**

Stainless, all reading parts glare-free satin chrome-plated. Barrel with jet black scale and ratchet. For through holes, measuring faces of hardened steel.

**Supplied with:**

Internal micrometers No. 429000. Setting rings similar to No. 484030, extension 150 mm No. 429010.

Calibration: S6

Scale divisions: 0.005 mm

Error limit: 0,006 mm

Number of micrometers: 4

Setting ring  $\varnothing$ : 25 / 40 mm

**Technical description**

Number of micrometers	4
Measuring range	20 - 50 mm
Setting ring $\varnothing$	25 / 40 mm
Error limit	0,006 mm
Scale divisions	0.005 mm

Standard	DIN 863
Micrometer barrel graduations	1/50 mm
Measurement technology	analogue
Packaging	sturdy box
Calibration	S6
Type of product	3-point internal micrometers

### Services

Calibration Internal micrometer set Measuring range 20-50 mm	011240 20-50
Labelling laser-etched Type	018940

### Accessories

Setting ring DIN 2250 C Nominal size Ø 45 mm	484030 45
Setting ring DIN 2250 C Nominal size Ø 35 mm	484030 35
Setting ring DIN 2250 C Nominal size Ø 27 mm	484030 27
Internal micrometer Measuring range 25-30 mm	429000 25-30
Internal micrometer Measuring range 30-40 mm	429000 30-40
Setting ring DIN 2250 C Nominal size Ø 22 mm	484030 22
Extension for internal micrometer Type 3/150	429010 3/150
Internal micrometer Measuring range 40-50 mm	429000 40-50
Internal micrometer Measuring range 20-25 mm	429000 20-25