

## Mitutoyo

### Internal micrometer set Holtest for measuring blind holes, Measuring range: 12-20 mm



#### Order data

Order number	429055 12-20
GTIN	4946368517582
Item class	44A

#### Description

##### Version:

Stainless, all reading parts glare-free satin chrome-plated. Barrel with jet black scale and ratchet. Blind hole version. **Measuring faces of hardened steel with titanium coating for long tool life.**

##### Supplied with:

Internal micrometers No. 429005. Setting rings similar to No. 484030, extension 150 mm No. 429010.

Calibration: S6

Scale divisions: 0.005 mm

Error limit: 0,004 mm

Number of micrometers: 2

Setting ring  $\varnothing$ : 16 mm

#### Technical description

Measuring range	12 - 20 mm
Number of micrometers	2
Setting ring $\varnothing$	16 mm

Error limit	0,004 mm
Scale divisions	0.005 mm
Standard	Manufacturer's standard
Micrometer barrel graduations	1/50 mm
Measurement technology	analogue
Packaging	sturdy box
Calibration	S6
Type of product	3-point internal micrometers

### Services

Calibration Internal micrometer set Measuring range 12-20 mm	011240 12-20
Labelling laser-etched Type	018940
Calibration Internal micrometer set Measuring range 12-20 mm	020550 12-20

### Accessories

Setting ring DIN 2250 C Nominal size Ø 18 mm	484030 18
Internal micrometer Holtest for measuring blind holes Measuring range 16-20 mm	429005 16-20
Internal micrometer Holtest for measuring blind holes Measuring range 12-16 mm	429005 12-16
Extension for internal micrometer Type 2/150	429010 2/150
Setting ring DIN 2250 C Nominal size Ø 15 mm	484030 15