

**Mitutoyo**
**Internal micrometer set Holtest for measuring blind holes, Measuring range: 20-50 mm**


## Order data

Order number	429055 20-50
GTIN	4946368517599
Item class	44A

## Description

### Version:

Stainless, all reading parts glare-free satin chrome-plated. Barrel with jet black scale and ratchet. Blind hole version. **Measuring faces of hardened steel with titanium coating for long tool life.**

### Supplied with:

Internal micrometers No. 429005. Setting rings similar to No. 484030, extension 150 mm No. 429010.

Calibration: S6

Scale divisions: 0.005 mm

Error limit: 0,006 mm

Number of micrometers: 4

Setting ring  $\varnothing$ : 25 / 40 mm

## Technical description

Setting ring $\varnothing$	25 / 40 mm
Measuring range	20 - 50 mm
Number of micrometers	4

Error limit	0,006 mm
Scale divisions	0.005 mm
Standard	Manufacturer's standard
Micrometer barrel graduations	1/50 mm
Measurement technology	analogue
Packaging	sturdy box
Calibration	S6
Type of product	3-point internal micrometers

### Services

Calibration Internal micrometer set Measuring range 20-50 mm	011240 20-50
Labelling laser-etched Type	018940
Calibration Internal micrometer set Measuring range 20-50 mm	020550 20-50

### Accessories

Internal micrometer Holtest for measuring blind holes Measuring range 20-25 mm	429005 20-25
Internal micrometer Holtest for measuring blind holes Measuring range 30-40 mm	429005 30-40
Setting ring DIN 2250 C Nominal size Ø 45 mm	484030 45
Setting ring DIN 2250 C Nominal size Ø 35 mm	484030 35
Setting ring DIN 2250 C Nominal size Ø 27 mm	484030 27
Internal micrometer Holtest for measuring blind holes Measuring range 25-30 mm	429005 25-30
Internal micrometer Holtest for measuring blind holes Measuring range 40-50 mm	429005 40-50
Extension for internal micrometer Type 3/150	429010 3/150
Setting ring DIN 2250 C Nominal size Ø 22 mm	484030 22