

Mitutoyo
Small internal micrometer, Measuring range: 5-6 mm

Order data

Order number	429100 5-6
GTIN	4946368080505
Item class	44A

Description
Version:

Stainless, all reading parts glare-free satin chrome-plated. Barrel with jet black scale and ratchet. The micrometer head (**with 2 carbide measuring faces**) is adjusted by a **carbide-tipped** operating pin.

Application:

For accurate measurement of bore diameter and roundness.

Optional extras:

Setting rings No. 484030.

Calibration: B6

Scale divisions: 0.001 mm

Error limit: 0.002 mm

Barrel Ø: 17 mm

Measurement depth: 22 mm

Overall length: 115 mm

Technical description

Overall length	115 mm
Barrel Ø	17 mm
Measurement depth	22 mm
Measuring range	5 - 6 mm
Scale divisions	0.001 mm
Error limit	0.002 mm
Standard	Manufacturer's standard

Micrometer barrel graduations	1/50 mm
Measurement technology	analogue
Packaging	sturdy box
Calibration	B6
Type of product	2-point internal micrometer

Services

Calibration 3-point inside micrometer maximum measuring range 20 mm	012900 20
Labelling laser-etched Type	018940
DAkkS calibration 3-point internal micrometer maximum measuring range 200 mm	012910 200
Calibration 3-point inside micrometer maximum measuring range 20 mm	022500 20
DAkkS calibration 3-point internal micrometer maximum measuring range 200 mm	022510 200

Accessories

Setting ring DIN 2250 C Nominal size Ø 5 mm	484030 5
Setting ring DIN 2250 C Nominal size Ø 6 mm	484030 6