

**Mitutoyo****Digital internal micrometer set, Measuring range: 25-50 mm****Order data**

Order number	429112 25-50
GTIN	4946368562933
Item class	44A

**Description****Version:**

**Direct reading from clear digital display. Reliable and accurate measuring – without vernier.**

“Function Lock” prevents accidental displacement of the zero point.

Low power consumption. With battery charge status and error display.

**Measuring faces and wearing parts of carbide, from size 12 -25 measuring faces of hardened steel with titanium coating for long tool life.**

**Function:**

IP65: Protected against jets of water from all directions and protected against penetration by dust (dust-tight), also completely protected against touching.

**Supplied with:**

Digital internal micrometers No. 429110, setting rings.

Calibration: S6

IP Index of Protection: IP 65

Number of micrometers: 3

Number of setting rings: 2

Setting ring Ø: 30 / 40 mm

**Technical description**

Measuring range	25 - 50 mm
Number of setting rings	2
Setting ring Ø	30 / 40 mm
Number of micrometers	3
IP Index of Protection	IP 65
Power supply	Battery-powered
Standard	DIN 863
Interface	USB interface
Interface	Digimatic interface
Measurement technology	digital
Packaging	sturdy box
Calibration	S6
Type of product	3-point internal micrometer

## Services

Calibration Internal micrometer set Measuring range 25-50 mm	011240 25-50
Labelling laser-etched Type	018940
Calibration Internal micrometer set Measuring range 25-50 mm	020550 25-50

## Accessories

Setting ring DIN 2250 C Nominal size Ø 28 mm	484030 28
Button cell / special battery Battery type 357	081560 357
Setting ring DIN 2250 C Nominal size Ø 35 mm	484030 35
Multi-receiver / USB keyboard interface Type	498975
Connecting cable with data switch Type D2	497445 D2
Setting ring DIN 2250 C Nominal size Ø 45 mm	484030 45
Extension for internal micrometer Type 3/150	429010 3/150
Connecting cable with data switch Type USB2	497445 USB2

Receiver / USB keyboard interface Type	498965
Transmitter Type S16E	498966 S16E
Connecting cable with data switch Type D1	497445 D1