

Mitutoyo
Digital internal micrometer set, Measuring range: 6-12 mm

Order data

| | |
|--------------|---------------|
| Order number | 429112 6-12 |
| GTIN | 4946368562919 |
| Item class | 44A |

Description
Version:

Direct reading from clear digital display. Reliable and accurate measuring – without vernier.

“Function Lock” prevents accidental displacement of the zero point.

Low power consumption. With battery charge status and error display.

Measuring faces and wearing parts of carbide, from size 12 -25 measuring faces of hardened steel with titanium coating for long tool life.

Function:

IP65: Protected against jets of water from all directions and protected against penetration by dust (dust-tight), also completely protected against touching.

Supplied with:

Digital internal micrometers No. 429110, setting rings.

Calibration: S6

IP Index of Protection: IP 65

Number of micrometers: 3

Number of setting rings: 2

Setting ring Ø: 8 / 10 mm

Technical description

| | |
|-------------------------|-----------------------------|
| Setting ring Ø | 8 / 10 mm |
| Measuring range | 6 - 12 mm |
| Number of micrometers | 3 |
| Number of setting rings | 2 |
| IP Index of Protection | IP 65 |
| Power supply | Battery-powered |
| Standard | DIN 863 |
| Interface | USB interface |
| Interface | Digimatic interface |
| Measurement technology | digital |
| Packaging | sturdy box |
| Calibration | S6 |
| Type of product | 3-point internal micrometer |

Services

| | |
|---|-------------|
| Calibration Internal micrometer set Measuring range 6-12 mm | 011240 6-12 |
| Labelling laser-etched Type | 018940 |
| Calibration Internal micrometer set Measuring range 6-12 mm | 020550 6-12 |

Accessories

| | |
|--|--------------|
| Connecting cable with data switch Type USB2 | 497445 USB2 |
| Extension for internal micrometer Type 1/100 | 429010 1/100 |
| Receiver / USB keyboard interface Type | 498965 |
| Setting ring DIN 2250 C Nominal size Ø 11 mm | 484030 11 |
| Connecting cable with data switch Type D2 | 497445 D2 |
| Connecting cable with data switch Type D1 | 497445 D1 |
| Setting ring DIN 2250 C Nominal size Ø 9 mm | 484030 9 |
| Multi-receiver / USB keyboard interface Type | 498975 |

| | |
|--|-------------|
| Button cell / special battery Battery type 357 | 081560 357 |
| Setting ring DIN 2250 C Nominal size Ø 7 mm | 484030 7 |
| Transmitter Type S16E | 498966 S16E |