

Granite plate Accuracy class 1, Length×Width: 400X250 mm



Order data

Order number	430200 400X250
GTIN	2050001040077
Item class	46H

Description

Version:

Specially selected natural granite.

- · Free of flaws, homogeneous structure.
- · Deflection and torsion resistant.
- · Absolutely rustproof and resistant to acid, low thermal conductivity.
- Micro-fine surface treatment (diamond lapped). Tolerances tighter than recommended limits.
- Ground outside edges, visually true.
- For static determination of position, contact points (steel ball inserts) are fitted to the underside.
- · Harder than hardened steel (Mohs hardness scale 6 7), non-magnetic and electrically non-conductive.

Accuracy:

Final manufacturing and inspection take place in computer-controlled climatic rooms. The used measuring equipment guarantees the exact connection to national and international calibration laboratories.

DIN 876/1 – diamond lapped for workshop and production.

Supplied with:

Supplied with test certificate, transport packing. Including rubber feet.

Note:

On request: Stainless steel screw inserts, steel T-slot rails (steel T-slot rails not available for No. 430190), accuracy 000, other sizes, intermediate sizes. Delivery excluded.

Test certificate: Manufacturer's test certificate

Flatness: 0.014 mm Thickness: 50 mm

Number of rubber feet: 4

Weight: 15 kg



Technical description

Thickness	50 mm
Weight	15 kg
Flatness	0.014 mm
Number of rubber feet	4
Standard	DIN 876
Test certificate	Manufacturer's test certificate
Type of product	Natural granite measurement plate

Services

Labelling laser-etched Type	018940
DAkkS calibration Comparator stand maximum table size 400X400	023610 400X400
400X400	023600 400X400

Accessories

Cleaner for natural granite Contents 0,5 I	431841 0,5
Care product for granite Contents 0,5 kg	431840 0,5