

Granite plate Accuracy class 0, Length×Width: 1000X630 mm



Order data

Order number	430300 1000X630
GTIN	2050001949769
Item class	46H

Description

Version:

Specially selected natural granite.

- · Free of flaws, homogeneous structure.
- · Deflection and torsion resistant.
- · Absolutely rustproof and resistant to acid, low thermal conductivity.
- Micro-fine surface treatment (diamond lapped). Tolerances tighter than recommended limits.
- · Ground outside edges, visually true.
- For static determination of position, contact points (steel ball inserts) are fitted to the underside.
- · Harder than hardened steel (Mohs hardness scale 6 7), non-magnetic and electrically non-conductive.

Accuracy:

Final manufacturing and inspection take place in computer-controlled climatic rooms. The used measuring equipment guarantees the exact connection to national and international calibration laboratories.

DIN 876/0 – Precision diamond lapped for inspection.

Supplied with:

Supplied with test certificate, transport packing. Including steel ball inserts.

Note:

On request: Stainless steel screw inserts, steel T-slot rails (steel T-slot rails not available for No. 430190), accuracy 000, other sizes, intermediate sizes. Delivery excluded.

Test certificate: Manufacturer's test certificate

Flatness: 0.008 mm Thickness: 100 mm

Number of steel ball inserts: 3

Weight: 189 kg



Technical description

Flatness	0.008 mm
Thickness	100 mm
Weight	189 kg
Number of steel ball inserts	3
Standard	DIN 876
Test certificate	Manufacturer's test certificate
Type of product	Natural granite measurement plate

Accessories

Support frame for insert size length×width 1000X630 mm	431000 1000X630
Cleaner for natural granite Contents 0,5 l	431841 0,5
Care product for granite Contents 0,5 kg	431840 0,5
Support cabinet for insert size length×width 1000X630 mm	431050 1000X630