

PLANOLITH
Granite plate Accuracy class 0, Length×Width: 400X250 mm

Order data

Order number	430300 400X250
GTIN	2050001039088
Item class	46H

Description
Version:

Specially selected natural granite.

- **Free of flaws, homogeneous structure.**
- **Deflection and torsion resistant.**
- **Absolutely rustproof and resistant to acid, low thermal conductivity.**
- **Micro-fine surface treatment (diamond lapped). Tolerances tighter than recommended limits.**
- **Ground outside edges, visually true.**
- **For static determination of position, contact points (steel ball inserts) are fitted to the underside.**
- **Harder than hardened steel (Mohs hardness scale 6 - 7), non-magnetic and electrically non-conductive.**

Accuracy:

Final manufacturing and inspection take place in computer-controlled climatic rooms. The used measuring equipment guarantees the exact connection to national and international calibration laboratories.

DIN 876/0 – Precision diamond lapped for inspection.

Supplied with:

Supplied with test certificate, transport packing. Including rubber feet.

Note:

On request: Stainless steel screw inserts, steel T-slot rails (steel T-slot rails not available for No. 430190), accuracy 000, other sizes, intermediate sizes. Delivery excluded.

Test certificate: Manufacturer's test certificate

Flatness: 0.006 mm

Thickness: 50 mm

Number of rubber feet: 4

Weight: 15 kg

Technical description

Flatness	0.006 mm
Thickness	50 mm
Weight	15 kg
Number of rubber feet	4
Standard	DIN 876
Test certificate	Manufacturer's test certificate
Type of product	Natural granite measurement plate

Accessories

Cleaner for natural granite Contents 0,5 l	431841 0,5
Care product for granite Contents 0,5 kg	431840 0,5