PLAN@LITH

Granite plate Accuracy class 0, Length×Width: 400X400 mm



Order data

Order number	430300 400X400
GTIN	2050001040671
Item class	46H

Description

Version:

Specially selected natural granite.

- · Free of flaws, homogeneous structure.
- · Deflection and torsion resistant.
- · Absolutely rustproof and resistant to acid, low thermal conductivity.
- Micro-fine surface treatment (diamond lapped). Tolerances tighter than recommended limits.
- · Ground outside edges, visually true.
- For static determination of position, contact points (steel ball inserts) are fitted to the underside.
- Harder than hardened steel (Mohs hardness scale 6 7), non-magnetic and electrically non-conductive.

Accuracy:

Final manufacturing and inspection take place in computer-controlled climatic rooms. The used measuring equipment guarantees the exact connection to national and international calibration laboratories.

DIN 876/0 – Precision diamond lapped for inspection.

Supplied with:

Supplied with test certificate, transport packing. Including rubber feet.

Note:

On request: Stainless steel screw inserts, steel T-slot rails (steel T-slot rails not available for No. 430190), accuracy 000, other sizes, intermediate sizes. Delivery excluded.

Test certificate: Manufacturer's test certificate

Flatness: 0.006 mm

Thickness: 50 mm

Number of rubber feet: 4

Weight: 25 kg

Technical description

Weight	25 kg
Thickness	50 mm
Flatness	0.006 mm
Number of rubber feet	4
Standard	DIN 876
Test certificate	Manufacturer's test certificate
Type of product	Natural granite measurement plate

Services

Labelling laser-etched Type	018940
DAkkS calibration Comparator stand maximum table size 400X400	023610 400X400
400X400	023600 400X400

Accessories

Care product for granite Contents 0,5 kg	431840 0,5
Cleaner for natural granite Contents 0,5 l	431841 0,5