

Granite plate Accuracy class 00, Length×Width: 400X400 mm



Order data

| Order number | 430400 400X400 |
|--------------|----------------|
| GTIN | 2050001042613 |
| Item class | 46H |

Description

Version:

Specially selected natural granite.

- · Free of flaws, homogeneous structure.
- · Deflection and torsion resistant.
- · Absolutely rustproof and resistant to acid, low thermal conductivity.
- Micro-fine surface treatment (diamond lapped). Tolerances tighter than recommended limits.
- · Ground outside edges, visually true.
- For static determination of position, contact points (steel ball inserts) are fitted to the underside.
- · Harder than hardened steel (Mohs hardness scale 6 7), non-magnetic and electrically non-conductive.

Accuracy:

Final manufacturing and inspection take place in computer-controlled climatic rooms. The used measuring equipment guarantees the exact connection to national and international calibration laboratories.

DIN 876/00 – High precision diamond lapped for measuring room.

Supplied with:

Supplied with test certificate, transport packing. Including rubber feet.

Note:

On request: Stainless steel screw inserts, steel T-slot rails (steel T-slot rails not available for No. 430190), accuracy 000, other sizes, intermediate sizes. Delivery excluded.

Test certificate: Manufacturer's test certificate

Flatness: 0.003 mm Thickness: 50 mm

Number of rubber feet: 4

Weight: 25 kg



Technical description

| Weight | 25 kg |
|-----------------------|-----------------------------------|
| Flatness | 0.003 mm |
| Thickness | 50 mm |
| Number of rubber feet | 4 |
| Standard | DIN 876 |
| Test certificate | Manufacturer's test certificate |
| Type of product | Natural granite measurement plate |

Accessories

| Care product for granite Contents 0,5 kg | 431840 0,5 |
|--|------------|
| Cleaner for natural granite Contents 0,5 l | 431841 0,5 |