PLAN@LITH

Granite plate Accuracy class 00, Length×Width: 630X630 mm



Order data

Order number	430400 630X630
GTIN	2050001042637
Item class	46H

Description

Version:

Specially selected natural granite.

- · Free of flaws, homogeneous structure.
- · Deflection and torsion resistant.
- $\cdot\,$ Absolutely rustproof and resistant to acid, low thermal conductivity.
- Micro-fine surface treatment (diamond lapped). Tolerances tighter than recommended limits.
- · Ground outside edges, visually true.
- For static determination of position, contact points (steel ball inserts) are fitted to the underside.
- Harder than hardened steel (Mohs hardness scale 6 7), non-magnetic and electrically non-conductive.

Accuracy:

Final manufacturing and inspection take place in computer-controlled climatic rooms. The used measuring equipment guarantees the exact connection to national and international calibration laboratories.

DIN 876/00 – High precision diamond lapped for measuring room.

Supplied with:

Supplied with test certificate, transport packing. Including steel ball inserts. **Note:**

Note:

On request: Stainless steel screw inserts, steel T-slot rails (steel T-slot rails not available for No. 430190), accuracy 000, other sizes, intermediate sizes. Delivery excluded.

Test certificate: Manufacturer's test certificate

Flatness: 0.003 mm

Thickness: 70 mm

Number of steel ball inserts: 3

Weight: 83 kg

018940

Technical description

Flatness	0.003 mm
Thickness	70 mm
Weight	83 kg
Number of steel ball inserts	3
Standard	DIN 876
Test certificate	Manufacturer's test certificate
Type of product	Natural granite measurement plate

Services

Accessories

Care product for granite Contents 0,5 kg	431840 0,5
Support cabinet for insert size length×width 630X630 mm	431050 630X630
Cleaner for natural granite Contents 0,5 l	431841 0,5
Support frame for insert size length×width 630X630 mm	431000 630X630