



Dial indicator shock-resistant, Measuring range / Body Ø: 10/58 mm



Order data

Order number	432120 10/58
GTIN	2050001037794
Item class	43A

Description

Version:

Dimensions to DIN EN ISO 463, issue June 2006. **Shock-resistant** precision dial indicators. Clamping shank Ø 8 mm h6, hardened and ground. Outer ring of dial face can be rotated to zero the dial. Outer ring with 2 adjustable tolerance pointers. Central pointer for 1/100 mm reading, small pointer on sub-scale for 1 mm reading.

Shock-resistant by rack sleeve. Chrome-plated protective casing with integrated back.

Optional extras:

Special contact points No. 434900; 434910; 434915.

Packaging: sturdy box

Standard: DIN 878

Calibration: C1

Graduation: 0.01 mm

Reading per pointer revolution: 1 mm

Gauging force: 0.7 - 1.5 N

Technical description

Calibration	C1
-------------	----

Reading per pointer revolution	1 mm
Measuring range	10 mm
Gauging force	0.7 - 1.5 N
Graduation	0.01 mm
Body Ø	58 mm
Standard	DIN 878
Measurement technology	analogue
Packaging	sturdy box
Type of product	Dial Indicator

Services

Calibration Dial indicator analogue 0.01 and digital 0.01 / 0.001 maximum measuring span 10 mm	013210 10
Labelling laser-etched Type	018940
DAkkS calibration Dial indicator analogue 0.01 and digital 0.01 / 0.001 maximum measuring span 12,5 mm	013250 12,5

Accessories

Ruby contact point Type 2	434915 2
Steel contact point Type 2	434900 2
Carbide contact point Type 2	434910 2
Carbide contact point Type 18/2	434910 18/2
Steel contact point Type 15	434900 15
Extension for measuring probe Length L 10 mm	434920 10
Carbide contact point Type 18/6	434910 18/6
Steel contact point Type 12	434900 12
Carbide contact point Type 14	434910 14
Extension for measuring probe Length L 100 mm	434920 100
Steel contact point Type 20	434900 20
Carbide contact point Type 18/1	434910 18/1

Steel contact point Type 14/40	434900 14/40
Steel contact point Type 18/2	434900 18/2
Pivoting contact point	434912
Angled bracket for dial indicator 45° Clamping length 50 mm	434917 50
Steel contact point Type 14	434900 14
Extension for measuring probe Length L 50 mm	434920 50
Carbide contact point Type 10	434910 10
Carbide contact point Type 18/5	434910 18/5
Steel contact point Type 18/6	434900 18/6
Extension for measuring probe Length L 30 mm	434920 30
Carbide contact point Type 18/4	434910 18/4
Steel contact point Type 10	434900 10
Angled bracket for dial indicator 45° Clamping length 25 mm	434917 25
Carbide contact point Type 16	434910 16
Steel contact point Type 29/10	434900 29/10
Angled bracket for dial indicator 60° Clamping length 25 mm	434918 25
Steel contact point Type 11/25	434900 11/25
Steel contact point Type 11	434900 11
Extension for measuring probe Length L 90 mm	434920 90
Extension for measuring probe Length L 60 mm	434920 60
Steel contact point Type 18/3	434900 18/3
Carbide contact point Type 17	434910 17
Steel contact point Type 11/20	434900 11/20
Steel contact point Type 11/15	434900 11/15
Extension for measuring probe Length L 40 mm	434920 40
Steel contact point Type 16	434900 16
Steel contact point Type 29/20	434900 29/20

Steel contact point Type 24	434900 24
Extension for measuring probe Length L 80 mm	434920 80
Steel contact point Type 18/1	434900 18/1
Steel contact point Type 11/35	434900 11/35
Steel contact point Type 30/10	434900 30/10
Angled bracket for dial indicator 60° Clamping length 50 mm	434918 50
Carbide contact point Type 11	434910 11
Steel contact point Type 28	434900 28
Steel contact point Type 13	434900 13
Extension for measuring probe Length L 70 mm	434920 70
Steel contact point Type 18/4	434900 18/4
Carbide contact point Type 18/3	434910 18/3
Steel contact point Type 39	434900 39
Steel contact point Type 17	434900 17
Steel contact point Type 14/30	434900 14/30
Steel contact point Type 14/15	434900 14/15
Steel contact point Type 11/30	434900 11/30
Steel contact point Type 18/5	434900 18/5
Extension for measuring probe Length L 15 mm	434920 15
Steel contact point Type 14/20	434900 14/20
Extension for measuring probe Length L 20 mm	434920 20