

Garant
**Precision dial indicator IP67, shock-resistant, Measuring range / Body Ø:
10/58 mm**

Order data

| | |
|--------------|---------------|
| Order number | 432210 10/58 |
| GTIN | 4045197154071 |
| Item class | 41C |

Description
Version:

Dial indicators with protection **against splashed water, oil and dirt**. Contact point on plunger spindle sealed by rubber bellows, sealed by protective sleeve at the top. Back wall sealed, glass and outer ring tightly screwed. Clamping shank \varnothing 8 mm h6.

Standard:

Shock-resistant precision dial indicators. Clamping shank \varnothing 8 mm h6, hardened and ground. Outer ring of dial face can be rotated to zero the dial. Outer ring with 2 adjustable tolerance pointers. Central pointer for 1/100 mm reading, small pointer on sub-scale for 1 mm reading.

Function:

IP67: Protected against intermittent immersion in water and protected against penetration by dust (dust-tight), also completely protected against touching.

Optional extras:

Special contact points No. 434900; 434910; 434915.

Packaging: sturdy box

Standard: DIN 878

IP Index of Protection: IP 67

Calibration: C1

Graduation: 0.01 mm

Reading per pointer revolution: 1 mm

Gauging force: 0.9 - 1.6 N

Technical description

| | |
|--------------------------------|----------------|
| Graduation | 0.01 mm |
| Body Ø | 58 mm |
| Gauging force | 0.9 - 1.6 N |
| Reading per pointer revolution | 1 mm |
| Measuring range | 10 mm |
| Calibration | C1 |
| Standard | DIN 878 |
| IP Index of Protection | IP 67 |
| Rotatable dial face | yes |
| adjustable tolerance marks | yes |
| Measurement technology | analogue |
| Packaging | sturdy box |
| Type of product | Dial Indicator |

Services

| | |
|--|-------------|
| Calibration Dial indicator analogue 0.01 and digital 0.01 / 0.001 maximum measuring span 10 mm | 013210 10 |
| Labelling laser-etched Type | 018940 |
| DAkkS calibration Dial indicator analogue 0.01 and digital 0.01 / 0.001 maximum measuring span 12,5 mm | 013250 12,5 |
| DAkkS calibration Dial indicator analogue 0.01 and digital 0.01 / 0.001 maximum measuring span 12,5 mm | 023010 12,5 |
| Calibration Dial indicator analogue 0.01 and digital 0.01 / 0.001 maximum measuring span 10 mm | 023000 10 |

Accessories

| | |
|-----------------------------|-----------|
| Steel contact point Type 20 | 434900 20 |
|-----------------------------|-----------|

| | |
|---|--------------|
| Extension for measuring probe Length L 15 mm | 434920 15 |
| Steel contact point Type 24 | 434900 24 |
| Steel contact point Type 14 | 434900 14 |
| Carbide contact point Type 16 | 434910 16 |
| Carbide contact point Type 18/6 | 434910 18/6 |
| Steel contact point Type 11/30 | 434900 11/30 |
| Extension for measuring probe Length L 20 mm | 434920 20 |
| Pivoting contact point | 434912 |
| Steel contact point Type 15 | 434900 15 |
| Carbide contact point Type 18/3 | 434910 18/3 |
| Carbide contact point Type 18/5 | 434910 18/5 |
| Extension for measuring probe Length L 100 mm | 434920 100 |
| Steel contact point Type 29/20 | 434900 29/20 |
| Steel contact point Type 14/15 | 434900 14/15 |
| Extension for measuring probe Length L 60 mm | 434920 60 |
| Steel contact point Type 14/40 | 434900 14/40 |
| Steel contact point Type 18/4 | 434900 18/4 |
| Steel contact point Type 18/3 | 434900 18/3 |
| Steel contact point Type 39 | 434900 39 |
| Steel contact point Type 29/10 | 434900 29/10 |
| Extension for measuring probe Length L 70 mm | 434920 70 |
| Steel contact point Type 18/2 | 434900 18/2 |
| Steel contact point Type 12 | 434900 12 |
| Extension for measuring probe Length L 10 mm | 434920 10 |
| Steel contact point Type 18/6 | 434900 18/6 |
| Steel contact point Type 30/10 | 434900 30/10 |
| Steel contact point Type 11/15 | 434900 11/15 |
| Extension for measuring probe Length L 30 mm | 434920 30 |
| Carbide contact point Type 18/4 | 434910 18/4 |

| | |
|---|--------------|
| Carbide contact point Type 11 | 434910 11 |
| Steel contact point Type 11/35 | 434900 11/35 |
| Dial indicator glass Type 58 | 432010 58 |
| Ruby contact point Type 2 | 434915 2 |
| Steel contact point Type 2 | 434900 2 |
| Steel contact point Type 14/20 | 434900 14/20 |
| Carbide contact point Type 10 | 434910 10 |
| Carbide contact point Type 2 | 434910 2 |
| Steel contact point Type 14/30 | 434900 14/30 |
| Steel contact point Type 11 | 434900 11 |
| Carbide contact point Type 18/1 | 434910 18/1 |
| Steel contact point Type 11/20 | 434900 11/20 |
| Carbide contact point Type 18/2 | 434910 18/2 |
| Steel contact point Type 13 | 434900 13 |
| Angled bracket for dial indicator 60° Clamping length 25 mm | 434918 25 |
| Steel contact point Type 28 | 434900 28 |
| Extension for measuring probe Length L 80 mm | 434920 80 |
| Carbide contact point Type 17 | 434910 17 |
| Angled bracket for dial indicator 45° Clamping length 50 mm | 434917 50 |
| Steel contact point Type 10 | 434900 10 |
| Steel contact point Type 11/25 | 434900 11/25 |
| Extension for measuring probe Length L 90 mm | 434920 90 |
| Angled bracket for dial indicator 60° Clamping length 50 mm | 434918 50 |
| Extension for measuring probe Length L 50 mm | 434920 50 |
| Extension for measuring probe Length L 40 mm | 434920 40 |
| Angled bracket for dial indicator 45° Clamping length 25 mm | 434917 25 |
| Steel contact point Type 18/5 | 434900 18/5 |

| | |
|-------------------------------|-------------|
| Steel contact point Type 18/1 | 434900 18/1 |
| Steel contact point Type 16 | 434900 16 |
| Steel contact point Type 17 | 434900 17 |
| Carbide contact point Type 14 | 434910 14 |