



Safety dial indicator, Measuring range / Body Ø: 0,16/58 mm



Order data

Order number	432405 0,16/58
GTIN	4031452101843
Item class	46C

Description

Version:

Dimensions to DIN EN ISO 463, issue June 2006. Precision dial indicators, shockproof, safety dial indicators, shockproof, with overrun. Extremely light, robust construction, dustproof. Clamping shank Ø 8 mm h6.

Highest precision due to combined gear and lever mechanism.

Packaging: sturdy box

Standard: Manufacturer's standard

Calibration: C2

Graduation: 0.001 mm

Variation range f_e : 2 µm

Gauging force: 1.3 - 1.8 N

Free stroke: 4.5 mm

Technical description

Graduation	0.001 mm
Measuring range	0.16 mm
Free stroke	4.5 mm

Gauging force	1.3 - 1.8 N
Calibration	C2
Clamping shank \varnothing h6	8 mm
Variation range f_e	2 μ m
Standard	Manufacturer's standard
Measurement technology	analogue
Packaging	sturdy box
Type of product	Dial Indicator

Services

Calibration Dial indicator, analogue 0.001 maximum measuring span 5 mm	013220 5
Labelling laser-etched Type	018940
Calibration Dial indicator, analogue 0.001 maximum measuring span 5 mm	023020 5