



## Safety dial indicator, Measuring range / Body Ø: 0,8/58 mm



### Order data

Order number	432405 0,8/58
GTIN	2050001741073
Item class	46C

### Description

#### Version:

Dimensions to DIN EN ISO 463, issue June 2006. Precision dial indicators, shockproof, safety dial indicators, shockproof, with overrun. Extremely light, robust construction, dustproof. Clamping shank Ø 8 mm h6.

Highest precision due to combined gear and lever mechanism.

Packaging: sturdy box

Standard: DIN 878

Calibration: C1

Graduation: 0.01 mm

Variation range  $f_e$ : 7 µm

Gauging force: 0.8 - 1.2 N

Free stroke: 7 mm

### Technical description

Gauging force	0.8 - 1.2 N
Calibration	C1
Body Ø	58 mm

Graduation	0.01 mm
Measuring range	0.8 mm
Variation range $f_e$	7 $\mu\text{m}$
Free stroke	7 mm
Standard	DIN 878
Measurement technology	analogue
Packaging	sturdy box
Type of product	Dial Indicator

### Services

Labelling laser-etched Type	018940
DAkkS calibration Dial indicator analogue 0.01 and digital 0.01 / 0.001 maximum measuring span 12,5 mm	013250 12,5
Calibration Dial indicator analogue 0.01 and digital 0.01 / 0.001 maximum measuring span 3 mm	013210 3
Calibration Dial indicator analogue 0.01 and digital 0.01 / 0.001 maximum measuring span 3 mm	023000 3
DAkkS calibration Dial indicator analogue 0.01 and digital 0.01 / 0.001 maximum measuring span 12,5 mm	023010 12,5