



## Digital dial indicator 0.01 mm reading, Measuring range: 25 mm



### Order data

Order number	434004 25
GTIN	4062406272500
Item class	42C

### Description

#### Version:

Digital dial indicator in compact design with high-contrast digital display.

- **Reversible direction of measurement.**
- **Very narrow casing.**

#### Standard:

Digital dial indicator in compact design with high-contrast digital display.

#### Supplied with:

Supplied with an eye on the cover and 1 battery No. 081560 size CR2032.

#### Optional extras:

Spare and special contact points No. 434900 / 4910 / 4915.

Packaging: sturdy box

Calibration: C1

Reversible reading: 0.01 mm

Reversible reading: 0.0005 inch

Error limit: 0.035 mm

Gauging force: 0.8 – 1.7 N

Clamping shank - Ø h7: 8 mm

Body Ø: 58 mm

## Technical description

Reversible reading	0.0005 inch
Clamping shank - Ø h7	8 mm
Error limit	0.035 mm
Gauging force	0.8 – 1.7 N
Measuring range	0 - 25 mm
Body Ø	58 mm
Calibration	C1
Number of batteries contained	1
Reversible reading	0.01 mm
Thickness of housing	26 mm
Article no of the battery / rechargeable battery fitted	081560 CR2032
Power supply	Battery-powered
Standard	Manufacturer's standard
Reversible reading	mm / inch
Measurement technology	digital
Packaging	sturdy box
Type of product	Dial Indicator

## Services

Labelling laser-etched Type	018940
Calibration Dial indicator analogue 0.01 and digital 0.01 / 0.001 maximum measuring span 30 mm	013210 30
DAkkS calibration Dial indicator analogue 0.01 and digital 0.01 / 0.001 maximum measuring span 100 mm	013250 100

## Accessories

Button cell / special battery International size CR2032	081560 CR2032
Steel contact point Type 10	434900 10

Steel contact point Type 11	434900 11
Steel contact point Type 12	434900 12
Steel contact point Type 13	434900 13
Steel contact point Type 14	434900 14
Steel contact point Type 15	434900 15
Steel contact point Type 16	434900 16
Steel contact point Type 17	434900 17
Steel contact point Type 2	434900 2
Steel contact point Type 20	434900 20
Steel contact point Type 24	434900 24
Steel contact point Type 28	434900 28
Steel contact point Type 39	434900 39
Carbide contact point Type 10	434910 10
Carbide contact point Type 11	434910 11
Carbide contact point Type 14	434910 14
Carbide contact point Type 16	434910 16
Carbide contact point Type 17	434910 17
Carbide contact point Type 2	434910 2
Pivoting contact point	434912
Ruby contact point Type 2	434915 2
Angled bracket for dial indicator 45° Clamping length 25 mm	434917 25
Angled bracket for dial indicator 45° Clamping length 50 mm	434917 50
Angled bracket for dial indicator 60° Clamping length 25 mm	434918 25
Angled bracket for dial indicator 60° Clamping length 50 mm	434918 50
Extension for measuring probe Length L 10 mm	434920 10
Extension for measuring probe Length L 100 mm	434920 100
Extension for measuring probe Length L 15 mm	434920 15

Extension for measuring probe Length L 20 mm	434920 20
Extension for measuring probe Length L 30 mm	434920 30
Extension for measuring probe Length L 40 mm	434920 40
Extension for measuring probe Length L 50 mm	434920 50
Extension for measuring probe Length L 60 mm	434920 60
Extension for measuring probe Length L 70 mm	434920 70
Extension for measuring probe Length L 80 mm	434920 80
Extension for measuring probe Length L 90 mm	434920 90