



Digital dial indicator 0.01 mm reading, Measuring range: 12,5 mm



Order data

Order number	434260 12,5
GTIN	7630041111170
Item class	45A

Description

Version:

Digital dial indicator with combined scale and digital display (10 mm character height) and mechanical tolerance marks.

Function:

Automatic switch-off, measurement value output, reversible direction of measurement. Button panel can be locked.

Supplied with:

1 battery No. 081560 size CR2032

Optional extras:

Spare and special contact points No. 434900; 434910; 434915. Data cable No. 498950.

Interface: USB interface

Calibration: C1

Reversible reading: 0.01 mm

Reversible reading: 0.0005 inch

Error limit: 0.02 mm

Gauging force: ≤ 2 N

Clamping shank \varnothing h6: 8 mm

Body \varnothing : 57 mm

Technical description

Gauging force	≤ 2 N
Thickness of housing	27 mm
Calibration	C1
Measuring range	12.5 mm
Body Ø	57 mm
Clamping shank Ø h6	8 mm
Reversible reading	0.0005 inch
Reversible reading	0.01 mm
Error limit	0.02 mm
Number of batteries contained	1
Article no of the battery / rechargeable battery fitted	081560 CR2032
Power supply	Battery-powered
Standard	DIN 878
Reversible reading	mm / inch
Interface	RS232C interface
Interface	USB interface
Measurement technology	digital
Type of product	Dial Indicator

Services

Calibration Dial indicator analogue 0.01 and digital 0.01 / 0.001 maximum measuring span 12,5 mm	013210 12,5
Labelling laser-etched Type	018940
DAkkS calibration Dial indicator analogue 0.01 and digital 0.01 / 0.001 maximum measuring span 12,5 mm	013250 12,5
DAkkS calibration Dial indicator analogue 0.01 and digital 0.01 / 0.001 maximum measuring span 12,5 mm	023010 12,5
Calibration Dial indicator analogue 0.01 and digital 0.01 / 0.001 maximum measuring span 12,5 mm	023000 12,5

Accessories

Steel contact point Type 15	434900 15
Angled bracket for dial indicator 45° Clamping length 25 mm	434917 25
Extension for measuring probe Length L 50 mm	434920 50
Receiver / USB keyboard interface Type	498965
Extension for measuring probe Length L 80 mm	434920 80
Extension for measuring probe Length L 100 mm	434920 100
Steel contact point Type 11	434900 11
Connection cable Duplex Type USB2	498950 USB2
Carbide contact point Type 18/3	434910 18/3
Steel contact point Type 14/20	434900 14/20
Carbide contact point Type 18/4	434910 18/4
Carbide contact point Type 16	434910 16
Extension for measuring probe Length L 15 mm	434920 15
Carbide contact point Type 18/6	434910 18/6
Steel contact point Type 11/30	434900 11/30
Pivoting contact point	434912
Steel contact point Type 14/30	434900 14/30
Steel contact point Type 18/2	434900 18/2
Multi-receiver / USB keyboard interface Type	498975
Carbide contact point Type 14	434910 14
Angled bracket for dial indicator 45° Clamping length 50 mm	434917 50
Steel contact point Type 18/4	434900 18/4
Carbide contact point Type 10	434910 10
Steel contact point Type 39	434900 39
Extension for measuring probe Length L 10 mm	434920 10
Connection cable Duplex Type 2	498950 2
Steel contact point Type 29/10	434900 29/10

Steel contact point Type 18/3	434900 18/3
Steel contact point Type 11/25	434900 11/25
Steel contact point Type 20	434900 20
Steel contact point Type 29/20	434900 29/20
Steel contact point Type 2	434900 2
Extension for measuring probe Length L 40 mm	434920 40
Extension for measuring probe Length L 20 mm	434920 20
Extension for measuring probe Length L 70 mm	434920 70
Steel contact point Type 18/6	434900 18/6
Steel contact point Type 11/35	434900 11/35
Steel contact point Type 11/20	434900 11/20
Button cell / special battery Battery type CR2032	081560 CR2032
Steel contact point Type 10	434900 10
Steel contact point Type 14/40	434900 14/40
Carbide contact point Type 17	434910 17
Extension for measuring probe Length L 90 mm	434920 90
Steel contact point Type 18/5	434900 18/5
Steel contact point Type 14/15	434900 14/15
Steel contact point Type 13	434900 13
Steel contact point Type 12	434900 12
Steel contact point Type 14	434900 14
Steel contact point Type 16	434900 16
Ruby contact point Type 2	434915 2
Angled bracket for dial indicator 60° Clamping length 50 mm	434918 50
Carbide contact point Type 18/1	434910 18/1
Steel contact point Type 18/1	434900 18/1
Extension for measuring probe Length L 60 mm	434920 60
Angled bracket for dial indicator 60° Clamping length 25 mm	434918 25

Carbide contact point Type 18/2	434910 18/2
Steel contact point Type 24	434900 24
Carbide contact point Type 2	434910 2
Carbide contact point Type 18/5	434910 18/5
Steel contact point Type 17	434900 17
Extension for measuring probe Length L 30 mm	434920 30
Steel contact point Type 11/15	434900 11/15
Carbide contact point Type 11	434910 11
Steel contact point Type 28	434900 28
Transmitter Type S6	498966 S6
Steel contact point Type 30/10	434900 30/10