



Digital dial indicator IP54 0.0005 mm reading, Measuring range: 12,5 mm



Order data

Order number	434316 12,5
GTIN	4059192014582
Item class	43A

Description

Version:

Digital dial gauge with **very large** numeric display (**11 mm**) and integrated tolerance display (with or without measured value display).

Absolute function:

Zeroing possible in any position, without losing the reference value.

Factor adjustable with indication in the display.

Individual functions can be blocked directly at the digital indicator. Settings and saved values (factor, preset, tolerances) are not lost even when changing the battery.

Dust-proof and splashproof version IP 54.

Function:

IP54: Protected against splashed water from all directions and protected against penetration of dust into the inside (protected against dust), also completely protected against touching.

Supplied with:

1 battery No. 081560 size CR 2450.

Optional extras:

Data cable No. 498940.

Measured value saving: MAHR reference-lock system

IP Index of Protection: IP 54

Calibration: C1

Reversible reading: 0.0005 mm

Reversible reading: 0.00002 inch
 Error limit: 0.005 mm
 Error limit partial measurement range: 0.002 mm
 Gauging force: 0.65-0.90 N
 Clamping shank \varnothing h6: 8 mm

Technical description

Measuring range	12.5 mm
Calibration	C1
Clamping shank \varnothing h6	8 mm
Thickness of housing	35 mm
Body \varnothing	58 mm
Gauging force	0.65-0.90 N
Reversible reading	0.00002 inch
Reversible reading	0.0005 mm
Error limit	0.005 mm
IP Index of Protection	IP 54
Error limit partial measurement range	0.002 mm
Number of batteries contained	1
Article no of the battery / rechargeable battery fitted	081560 CR2450
Power supply	Battery-powered
Standard	Manufacturer's standard
Reversible reading	mm / inch
Interface	Digimatic interface
Interface	USB interface
Interface	RS232 interface
Measured value saving	MAHR reference-lock system
Measurement technology	digital
Type of product	Dial Indicator

Services

Calibration Dial indicator analogue 0.01 and digital 0.01 / 0.001 maximum measuring span 12,5 mm	013210 12,5
Labelling laser-etched Type	018940
DAkkS calibration Dial indicator analogue 0.01 and digital 0.01 / 0.001 maximum measuring span 12,5 mm	013250 12,5
Calibration Dial indicator analogue 0.01 and digital 0.01 / 0.001 maximum measuring span 12,5 mm	023000 12,5
DAkkS calibration Dial indicator analogue 0.01 and digital 0.01 / 0.001 maximum measuring span 12,5 mm	023010 12,5

Accessories

Connecting cable Type D2	498940 D2
Multi-receiver / USB keyboard interface Type	498975
Transmitter Type S4E	498966 S4E
Receiver / USB keyboard interface Type	498965
Connecting cable Type R2	498940 R2
Connecting cable Type USB2	498940 USB2
Button cell / special battery Battery type CR2450	081560 CR2450