



Inductive length measuring probe, axial Pack of 10 pcs., Type: GT21



Order data

Order number	434776 GT21
GTIN	7630041113457
Item class	45A

Description

Version:

Versatile precision length contact point.

- **Precision ball-bearing longitudinal measuring pin.**
- **High precision due to electronic measurement signal amplification.**
- **Clamping shank \varnothing 8 mm, can be clamped on the entire length.**
- **Due to ball bearings, resistant to fluctuations in temperature and lateral forces.**
- **Outstanding electro magnetic screening.**

The TESA length measurement probe is characterised by excellent repeatability, consistency and a long working life.

Function:

IP65: Protected against jets of water from all directions and protected against penetration by dust (dust-tight), also completely protected against touching.

Application:

Universally applicable for all high precision measurement tasks, particularly in workshop and manufacturing shop areas.

Supplied with:

Pack of 10 \times contact points No. 434775.

Optional extras:

Measuring tips, measuring force springs.

Calibration: Price on request

IP Index of Protection: IP 65

Measuring range: ± 1 mm

Repeatability: 0.01 μ m

Linearity error limit (L = meas. length in mm): $0.2 + 3 \times L^3$ μ m

Compatibility: TESA

Measuring force at electrical zero: 0.63 N

Technical description

Repeatability	0.01 µm
Measuring force at electrical zero	0.63 N
Measuring range	±1 mm
Manufacturer's designation	GT21
Compatibility	TESA
Linearity error limit (L = meas. length in mm)	$0.2 + 3 \times L^3 \mu\text{m}$
Measurement pin lifting	mechanical
Contact point travel	4.3 mm
Protective bellows	Nitrile
IP Index of Protection	IP 65
Calibration	Price on request
Type of product	Inductive length measuring probe

Services

Labelling laser-etched Type	018940
-----------------------------	--------