



Dial indicator with anticlockwise scale, Measuring range: 30 mm



Order data

Order number	434807 30
GTIN	4031452160765
Item class	46C

Description

Version:

Precision dial indicator with metal housing, clamping shank \varnothing 8 mm h6, hardened and ground. With **anticlockwise scale** for use with depth gauge bases and precision bore gauges.

Suitable for :

Depth gauges No. 434805

Packaging: sturdy box

Standard: Manufacturer's standard

Calibration: C1

Graduation: 0.01 mm

Reading per pointer revolution: 1 mm

Probe plunger \varnothing : 5 mm

Dial indicator \varnothing : 58 mm

Gauging force: 0.8 - 1.6 N

Technical description

Graduation	0.01 mm
Reading per pointer revolution	1 mm

Body Ø	57 mm
Calibration	C1
Gauging force	0.8 - 1.6 N
Measuring range	0 - 30 mm
Standard	Manufacturer's standard
Probe plunger Ø	5 mm
Dial indicator Ø	58 mm
Measurement technology	analogue
Packaging	sturdy box
Type of product	Dial Indicator

Services

Calibration Dial indicator analogue 0.01 and digital 0.01 / 0.001 maximum measuring span 30 mm	013210 30
Labelling laser-etched Type	018940
DAkkS calibration Dial indicator analogue 0.01 and digital 0.01 / 0.001 maximum measuring span 100 mm	023010 100
Calibration Dial indicator analogue 0.01 and digital 0.01 / 0.001 maximum measuring span 30 mm	023000 30