



Bore plug gauge for through holes OD, Sleeve Ø D: 30-40 mm



Order data

Order number	435156 30-40
GTIN	2050001677129
Item class	46D

Description

IMPORTANT: item is configurable

Quality: 10 mm; 11 mm; 12 mm; 13 mm; 6 mm; 7 mm; 8 mm; 9 mm

Tolerance zone: A; B; C; CD; D; E; EF; F; FG; G; H; J; JS; K; M; N; P; R; S; T; U; V; Z; ZA; ZB; ZC; ZC

Nominal size: 30 - 40 mm, Intervall: 0,001

Version:

OD bore plug gauges are mechanical two-point dial bore plug gauges for highest requirements. Hardened gauging sleeve. For bores of 2.5 – 100 mm. Centring by the gauging sleeve prevents tilt errors and therefore ensures maximum precision irrespective of the user. No need to seek the return point. Dial indicators with shank Ø 8 h6 can be used as displays.

- **Repetition accuracy 1 µm.**
- **Robust and reliable.**
- **Minimum measuring time with maximum measuring reliability.**
- **Thread connection bore gauge/ holder M10×1.**

Application:

For bores of 2.5 – 100 mm. For quality assurance in series production, manual or automatic measuring.

Supplied with:

Gauging sleeve with two radially movable 180° offset carbide measuring bars.

Optional extras:

Precision dial comparator No. 434674, inductive precision dial comparator No. 434670, dial indicator with anticlockwise scale 434807 size 10, digital dial indicator 434322, holder for plug gauges No. 435160, setting rings No. 484030. Measuring depth extensions, angle pieces and depth stops on request.

Note:

When ordering, please state **additionally** the exact bore tolerances, for example:

No. 435154 size 6–12 **10H7**,

No. 435154 size 6–12 **10 + 0.15 / – 0.01**,

No. 435154 size 6–12 **9.990 / 10.15**.

When using precision dial indicators, an additional extension No. 434920 size 10 or probe No. 434900 size 16 is required.

- **Plug gauges for large bores (up to Ø 200), recesses, grooves, also in 3-point version available on request.**
- **Tolerance range 10 µm or fine fit quality 5 and finer on request.**
- **Measuring range > 0.2 mm on request.**
- **Measuring contacts also available in ruby, ceramic and hard chrome plated.**

Calibration: C4

Repetition accuracy: 1 µm

Nominal size: 30 - 40 mm

Sleeve dimension H: 27 mm

Face dimension h: 10 mm

Gauging force: 2 N

Technical description

Gauging force	2 N
Repetition accuracy	1 µm
Face dimension h	10 mm
Sleeve dimension H	27 mm
Quality	6 mm
Quality	11 mm
Quality	8 mm
Quality	10 mm
Quality	7 mm
Quality	9 mm
Quality	12 mm
Quality	13 mm
Tolerance zone	V
Tolerance zone	FG
Tolerance zone	U
Tolerance zone	T

Tolerance zone	S
Tolerance zone	B
Tolerance zone	R
Tolerance zone	P
Tolerance zone	N
Tolerance zone	M
Tolerance zone	JS
Tolerance zone	K
Tolerance zone	J
Tolerance zone	H
Tolerance zone	A
Tolerance zone	G
Tolerance zone	FG
Tolerance zone	EF
Tolerance zone	F
Tolerance zone	E
Tolerance zone	D
Tolerance zone	CD
Tolerance zone	C
Tolerance zone	ZB
Tolerance zone	ZC
Tolerance zone	ZA
Tolerance zone	Z
Tolerance zone	ZC
Nominal size	30 - 40 mm
Calibration	C4
Type of product	Bore gauge micrometer head

Services

Calibration Precision bore gauge (types B + C) maximum measuring range 60 mm	013520 60
Labelling laser-etched Type	018940
DAkKS calibration Precision bore gauge (types B + C) maximum measuring range 60 mm	012930 60
DAkKS calibration Precision bore gauge (types B + C) maximum measuring range 60 mm	023220 60
Calibration Precision bore gauge (types B + C) maximum measuring range 60 mm	023210 60

Accessories

Setting ring DIN 2250 C Nominal size Ø 30 mm	484030 30
Holder for plug gauge OD Holder length 235 mm	435160 235
Precision dial comparator ± measuring range / reading 1500/50 µm	434674 1500/50
Setting ring DIN 2250 C Nominal size Ø 36 mm	484030 36
Inductive precision comparator Extramess Type 2100	434670 2100
Steel contact point Type 16	434900 16
Inductive precision comparator Extramess Type 2000	434670 2000
Precision dial comparator ± measuring range / reading 25/0,5 µm	434674 25/0,5
Precision dial comparator ± measuring range / reading 130/5 µm	434674 130/5
Precision dial comparator ± measuring range / reading 250/10 µm	434674 250/10
Setting ring DIN 2250 C Nominal size Ø 40 mm	484030 40
Inductive precision comparator Extramess Type 2001	434670 2001
Setting ring DIN 2250 C Nominal size Ø 32 mm	484030 32
Precision dial comparator ± measuring range / reading 50/1 µm	434674 50/1
Holder for plug gauge OD Holder length 50 mm	435160 50
Setting ring DIN 2250 C Nominal size Ø 35 mm	484030 35

Holder for plug gauge OD Holder length 105 mm	435160 105
Setting ring DIN 2250 C Nominal size Ø 34 mm	484030 34
Setting ring DIN 2250 C Nominal size Ø 38 mm	484030 38
Extension for measuring probe Length L 10 mm	434920 10