# **M**itutoyo

# Lever dial indicator contact point length 15.2 mm, Measuring range (reversible) / housing $\emptyset$ : 0,3/39 mm



#### Order data

Order number	436281 0,3/39
GTIN	4946368676296
Item class	44A

### **Description**

#### **Version:**

#### 2/1000 reading.

High-precision lever dial indicator with jewel-mounted mechanism, in handy, robust design. Housing and dovetail block are of one piece, which means that mounting is particularly rigid. Corrosion protection due to matt chrome-plated housing.

**Mitutoyo** – ruby mounted mechanism with carbide measurement ball. Unaffected by magnetic fields.

#### **Application:**

As an accurate dial bore gauge for testing variations from nominal size, testing concentricity, internal measurements, testing of parallelism, and flatness as well as for aligning components.

#### **Supplied with:**

Clamping spigot Ø 8 mm.

#### **Optional extras:**

Square holder No. 436510, centring holder No. 436512, articulated holder No. 359680.

#### **Spare part:**

Spare contact point with carbide or ruby ball available on request.

Calibration: C5

Scale divisions: 0.002 mm Variation range f<sub>e</sub>: 6 µm Total variation range  $f_{tot}$ : 11 µm Hysteresis error  $f_u$ : 3 µm Pivot range: 2×110 degrees

Gauging force: 0.4 N

# **Technical description**

Measuring range per direction	0.3 mm
Measurement ball Ø	2 mm
Clamping shank Ø h6	8 mm
Variation range f <sub>e</sub>	6 μm
Contact point length	15.2 mm
Gauging force	0.4 N
Total variation range f <sub>tot</sub>	11 μm
Pivot range	2×110 degrees
Body Ø	39 mm
Scale divisions	0.002 mm
Hysteresis error f <sub>u</sub>	3 μm
Standard	Manufacturer's standard
Measurement technology	analogue
Packaging	sturdy box
Calibration	C5
Type of product	Lever dial indicator

## Services

Calibration Lever dial indicator Type	013650
Labelling laser-etched Type	018940
DAkkS calibration Lever dial indicator Type	013660
Calibration Lever dial indicator Type ANALOG	023330 ANALOG
DAkkS calibration Lever dial indicator Type ANALOG	023340 ANALOG

## **Accessories**

Centring holder	436512
Square holder for small indicator	436510
Articulated holder Radius of action 120 mm	359680 120