



Lever dial indicator contact point length 14.5 mm, Measuring range per direction / Body Ø: 0,8/40 mm



Order data

Order number	436301 0,8/40
GTIN	4059192013608
Item class	43A

Description

Version:

High-precision lever dial indicator with jewel-mounted mechanism, in handy, robust design. Housing and dovetail block are of one piece, which means that mounting is particularly rigid. Corrosion protection due to matt chrome-plated housing.

With 1/100 reading.

Mahr – ruby mounted mechanism with carbide measurement ball. Contact point bearing in one-piece fork, therefore alignment is particularly exact; anti-magnetic.

Application:

As an accurate dial bore gauge for testing variations from nominal size, testing concentricity, internal measurements, testing of parallelism, and flatness as well as for aligning components.

Supplied with:

Clamping spigot Ø 8 mm.

Optional extras:

Square holder No. 436510, centring holder No. 436512, knuckle stand No. 359680.

Spare part:

Spare contact point with carbide or ruby ball available on request.

Note:

Additional information DIN 2270: Graduations 0.01 – deviation range 10 µm, total deviation range 13 µm, hysteresis error 3 µm.

Calibration: C5

Scale divisions: 0.01 mm

Pivot range: 2×110 degrees

Gauging force: 0.15 N

Clamping shank Ø h6: 8 mm

Technical description

Scale divisions	0.01 mm
Gauging force	0.15 N
Body Ø	40 mm
Measuring range per direction	0.8 mm
Pivot range	2×110 degrees
Clamping shank Ø h6	8 mm
Measurement ball Ø	2 mm
Standard	DIN 2270
Measurement technology	analogue
Packaging	sturdy box
Calibration	C5
Type of product	Lever dial indicator

Services

Calibration Lever dial indicator Type	013650
Labelling laser-etched Type	018940
DAkkS calibration Lever dial indicator Type	013660
Calibration Lever dial indicator Type ANALOG	023330 ANALOG
DAkkS calibration Lever dial indicator Type ANALOG	023340 ANALOG

Accessories

436371 2R

Carbide contact point, contact point length 14.5 mm Measurement ball Ø 2R mm	
Carbide contact point, contact point length 14.5 mm Measurement ball Ø 3 mm	436371 3
Spare glass for lever dial indicator External Ø 40 mm	436328 40
Stem and nut for lever dial indicator Shank Ø h6 4 mm	436311 4
Carbide contact point, contact point length 14.5 mm Measurement ball Ø 2 mm	436371 2
Square holder for small indicator	436510
Centring holder	436512
Carbide contact point, contact point length 14.5 mm Measurement ball Ø 1 mm	436371 1
Adjustable holder Shank Ø mm	436514
Stem and nut for lever dial indicator Shank Ø h6 8 mm	436311 8
Articulated holder Radius of action 120 mm	359680 120