

GIROD

Lever dial indicator contact point length 12.5 mm, Measuring range per direction / Body Ø: 0,07/40 mm

**Order data**

Order number	436424 0,07/40
GTIN	2050001709103
Item class	46Q

Description**Version:**

High-precision lever dial indicator in handy, robust design. Housing and dovetail block are of one piece, which means that mounting is particularly rigid. Corrosion protection due to matt chrome-plated housing. **1/1000 reading.**

Application:

As an accurate dial bore gauge for testing variations from nominal size, testing concentricity, internal measurements, testing of parallelism, and flatness as well as for aligning components.

Supplied with:

Clamping spigot Ø 8 mm.

Optional extras:

Square holder No. 436510, centring holder No. 436512, knuckle stand No. 359680.

Spare part:

Spare contact point with carbide or ruby ball available on request.

Note:

Additional information DIN 2270: Graduations 0.002/0.001 – deviation range 2 µm, total deviation range 4 µm, hysteresis error 2 µm.

Scale divisions: 0.001 mm

Pivot range: 2×110 degrees

Gauging force: 0.2 N

Clamping shank \varnothing h6: 8 mm

Technical description

Body \varnothing	40 mm
Measuring range per direction	0.07 mm
Scale divisions	0.001 mm
Gauging force	0.2 N
Pivot range	2×110 degrees
Clamping shank \varnothing h6	8 mm
Contact point length	12.5 mm
Measurement ball \varnothing	2 mm
Standard	DIN 2270
Measurement technology	analogue
Packaging	sturdy box
Calibration	C5
Type of product	Lever dial indicator

Services

Calibration Lever dial indicator Type	013650
Labelling laser-etched Type	018940
DAkkS calibration Lever dial indicator Type	013660
DAkkS calibration Lever dial indicator Type ANALOG	023340 ANALOG
Calibration Lever dial indicator Type ANALOG	023330 ANALOG

Accessories

Square holder for small indicator	436510
Carbide contact point contact point length 12.5 mm Measurement ball \varnothing 2 mm	436210 2
Centring holder	436512

Articulated holder Radius of action 120 mm

359680 120