



**Digital lever indicator, contact point length 14.5 mm, Measuring range per direction / Body Ø: 0,4/43 mm**



## Order data

Order number	436500 0,4/43
GTIN	4059192013301
Item class	43A

## Description

### Version:

Digital lever indicator with digital and analogue display **1/1000 reading.**

**Measurement mode.** Normal / MIN / MAX / MAX-MIN. A correction factor can be entered.

### Function:

IP65: Protected against jets of water from all directions and protected against penetration by dust (dust-tight), also completely protected against touching.

### Supplied with:

1 battery No. 081560 size CR2032, clamping spigot Ø 8 mm, contact point key, carbide contact point Ø 2 mm.

### Optional extras:

Data cable No. 498951. See No. 436210; 436240 for spare contact points.

Calibration: C5

IP Index of Protection: IP 65

Variation range  $f_e$ : 10 µm

Hysteresis error  $f_u$ : 5 µm

Pivot range: 2×110 degrees

Gauging force: 0.13 N

Clamping shank Ø h6: 8 mm

## Technical description

Gauging force	0.13 N
Hysteresis error $f_u$	5 $\mu$ m
Measuring range per direction	0.4 mm
Body $\varnothing$	43 mm
Variation range $f_e$	10 $\mu$ m
Pivot range	2×110 degrees
Clamping shank $\varnothing$ h6	8 mm
Contact point length	14.5 mm
Measurement ball $\varnothing$	2 mm
Number of batteries contained	1
Article no of the battery / rechargeable battery fitted	081560 CR2032
IP Index of Protection	IP 65
Power supply	Battery-powered
Standard	Manufacturer's standard
Reversible reading	mm / inch
Interface	USB interface
Interface	RS232 interface
Measurement technology	digital
Calibration	C5
Type of product	Lever dial indicator

## Services

Calibration Lever dial indicator Type	013650
Labelling laser-etched Type	018940
DAkkS calibration Lever dial indicator Type	013660
Calibration Lever dial indicator Type ANALOG	023330 ANALOG
DAkkS calibration Lever dial indicator Type ANALOG	023340 ANALOG

---

**Accessories**

Button cell / special battery Battery type CR2032	081560 CR2032
Connection cable Duplex Type R2	498951 R2
Carbide contact point contact point length 12.5 mm Measurement ball Ø 2 mm	436210 2
Carbide contact point contact point length 36.5 mm Measurement ball Ø 2 mm	436240 2
Connection cable Duplex Type USB2	498951 USB2