



## External quick caliper with dial gauge, Measuring range: 0-10 mm



### Order data

Order number	438545 0-10
GTIN	4045197634641
Item class	42C

### Description

#### Version:

1 fixed and 1 movable arm with carbide spherical contact points. The deflection of the moving contact point is transmitted to the dial indicator. The measured result can be read directly.

#### Application:

For quick measuring of external grooves, wall thicknesses, plates, pipe wall thicknesses, foils etc.

Calibration: C7

Scale divisions: 0.1 mm

Error limit: 0.1 mm

Carbide spherical point  $\varnothing$ : 2 mm

maximum contact point length L (measurement depth): 36 mm

Dial indicator  $\varnothing$ : 50 mm

### Technical description

Carbide spherical point $\varnothing$	2 mm
Scale divisions	0.1 mm
Measuring range	0 - 10 mm
Dial indicator $\varnothing$	50 mm
maximum contact point length L (measurement depth)	36 mm
Error limit	0.1 mm

Standard	Manufacturer's standard
Measurement technology	analogue
Calibration	C7
Type of product	External quick calipers

## Services

Calibration External / internal quick caliper	013850
Labelling laser-etched Type	018940
DAkkS calibration External / internal quick caliper	011320
Calibration External / internal quick caliper Type S	023450 S
DAkkS calibration External / internal quick caliper Type S	023460 S