


Kroepelin
Längenmesstechnik

External quick caliper with dial gauge, Measuring range: 0-10 mm



Order data

Order number	438555 0-10
GTIN	2050002040878
Item class	46Q

Description

Version:

1 fixed and 1 movable arm with carbide spherical contact points. The deflection of the moving contact point is transmitted to the dial indicator. The measured result can be read directly.

Function:

IP65: Protected against jets of water from all directions and protected against penetration by dust (dust-tight), also completely protected against touching.

Application:

For quick measuring of external grooves, wall thicknesses, plates, pipe wall thicknesses, foils etc.

Calibration: C7

IP Index of Protection: IP 65

Scale divisions: 0.005 mm

Error limit: 0.015 mm

Carbide spherical point \varnothing : 1.5 mm

maximum contact point length L (measurement depth): 35 mm

Dial indicator \varnothing : 65 mm

Technical description

maximum contact point length L (measurement depth)	35 mm
IP Index of Protection	IP 65
Scale divisions	0.005 mm
Measuring range	0 - 10 mm

Error limit	0.015 mm
Dial indicator Ø	65 mm
Carbide spherical point Ø	1.5 mm
Standard	Manufacturer's standard
Measurement technology	analogue
Calibration	C7
Type of product	External quick calipers

Services

DAkkS calibration External / internal quick caliper	011320
Labelling laser-etched Type	018940
Calibration External / internal quick caliper	013850