

Kroepelin
Längenmesstechnik

External quick caliper with dial gauge for pipes, Measuring range: 0-20 mm



Order data

| | |
|--------------|---------------|
| Order number | 438560 0-20 |
| GTIN | 2050001036773 |
| Item class | 46Q |

Description

Version:

1 fixed and 1 movable arm with carbide spherical contact points. The deflection of the moving contact point is transmitted to the dial indicator. The measured result can be read directly.

Function:

IP65: Protected against jets of water from all directions and protected against penetration by dust (dust-tight), also completely protected against touching.

Calibration: C7

IP Index of Protection: IP 65

Scale divisions: 0.01 mm

Error limit: 0.03 mm

Carbide spherical point \varnothing : 1.5 mm

minimum bore \varnothing : 10 mm

maximum contact point length L (measurement depth): 80 mm

Dial indicator \varnothing : 65 mm

Technical description

| | |
|--|-----------|
| Scale divisions | 0.01 mm |
| Measuring range | 0 - 20 mm |
| maximum contact point length L (measurement depth) | 80 mm |
| minimum bore \varnothing | 10 mm |
| Dial indicator \varnothing | 65 mm |

| | |
|-------------------------------------|-------------------------|
| Carbide spherical point \emptyset | 1.5 mm |
| IP Index of Protection | IP 65 |
| Error limit | 0.03 mm |
| Standard | Manufacturer's standard |
| Measurement technology | analogue |
| Calibration | C7 |
| Type of product | External quick calipers |

Services

| | |
|--|----------|
| Calibration External / internal quick caliper | 013850 |
| Labelling laser-etched Type | 018940 |
| DAkkS calibration External / internal quick caliper | 011320 |
| Calibration External / internal quick caliper Type S | 023450 S |
| DAkkS calibration External / internal quick caliper Type S | 023460 S |