

Hydraulic jointed arm (without magnetic base), Throat: 400 mm



Order data

Order number	440610 400
GTIN	4045197889591
Item class	41D

Description

Version:

Hydraulic measuring stand with central clamping - all joints are rigidly clamped by means of the central rotary knob. Oil hydraulics protected against oil leakage by double seals. Clamping force can be steplessly adjusted. **Large rubberised hand wheel** (\varnothing 54 mm) for easy tightening and releasing the clamp. Jointed arms on the dial indicator mounting rotates 360°, can be twisted 180° and suitable for dial indicators with shank \varnothing 6 and 8 mm or dovetail.

Callout:

Hydraulic central locking

with ergonomic handwheel

Fine adjustment

at the indicator holder

Ball joint

Magnetic base

in a plastic enclosure

Note:

Hydraulic stands can withstand large fluctuations in temperature when the clamp is open. However a certain time is required for the temperature of the oil to equalise. When the clamp is closed the maximum fluctuation in temperature without fluctuations in pressure is 15 °C. These can lead to damage to the stand or to the object that is clamped.

Throat: 400 mm

Connection thread: M8 Magnetic force: 1000 N



Technical description

Throat	400 mm
Connection thread	M8
Magnetic force	1000 N
Type of product	Measuring stand, hydraulic

Accessories

Magnetic base Type 1	440620 1
Replacement handwheel Type A	440626 A