



## Hydraulic stand arm (without base) with mechanical fine adjustment at the indicator holder, Throat: 260 mm



### Order data

Order number	440840 260
GTIN	4260180710069
Item class	46Q

### Description

#### Version:

**Hydraulic measuring stand with central clamping. One hand remains free for configuring the dial indicator.** All joints are rigidly clamped by the central button. Patented mechanism generates high pressure so that the hand wheel needs only slight force to close it. Oil hydraulics protected against oil leakage by double seals. Clamping force can be steplessly adjusted.

**Jointed arms** 360° rotatable on the dial indicator holder and 180° pivotable. **Dial indicator holder** for dial and digital indicators with shank Ø 8 mm or dovetail.

Only column **without** base.

#### Optional extras:

Magnetic base No. 440868 size 1.

#### Note:

Hydraulic measuring stands can withstand large fluctuations in temperature when the **clamp is open**. However a certain time is required for the temperature of the oil to equalise. When the **clamp is closed** the maximum fluctuation in temperature without major fluctuations in pressure is 15 °C. These can lead to damage to the stand or to the object that is clamped.

Throat: 260 mm

Connection thread: M8

Alignment of connecting thread: centre

Magnetic force: 800 N

### Technical description

Throat	260 mm
Magnetic force	800 N
Connection thread	M8
Alignment of connecting thread	centre
Type of product	Measuring stand, hydraulic

---

## Accessories

Adjustment screw M4×0.35 for dial indicator clamp	440859
Spare piston Type 4	440830 4
Clamping screw M3 for dial indicator clamp	440858
Sealing ring set Type 1	440855 1
Stand base Type 1	440868 1
Clamping handle Type 4	440850 4
Dial indicator clamp	440860