

PLANOLITH
Universal precision comparator stand with 3-D NOGA jointed arm, Table length×Width: 400X400 mm

Order data

Order number	442525 400X400
GTIN	2050001052469
Item class	46H

Description
Version:

Precision diamond lapped table, with test certificate. Solid 3D jointed arm with mechanical central clamping. Continuously adjustable clamping force with high stability. Quick and easy positioning. Universal indicator holder.

With fine adjustment, for clamping shank \varnothing 8 mm, \varnothing 6 mm, \varnothing 3/8 inch and indicators with dovetail clamping shanks.

Calibration: D1

Action radius of 3-D jointed arm: 600 mm

Length of jointed arm L_1 : 326 mm

Length of jointed arm L_2 : 242 mm

Connection thread: M10×1.25

Weight: 28 kg

Technical description

Weight	28 kg
Action radius of 3-D jointed arm	600 mm

Length of jointed arm L ₂	242 mm
Connection thread	M10×1.25
Length of jointed arm L ₁	326 mm
Standard	DIN 876/1
Test certificate	Manufacturer's test certificate
Calibration	D1
Type of product	Universal precision comparator stand

Services

Calibration Comparator stand maximum table size 400X400 mm	016220 400X400
Labelling laser-etched Type	018940
Calibration Comparator stand maximum table size 400X400 mm	024580 400X400

Accessories

3-D jointed arm Type 600	442110 600
3-D jointed arm Type 600	442114 600