

**Garant****Digital height gauge and marking-out system with data output, Marking height: 600 mm****Order data**

Order number	444000 600
GTIN	4045197889836
Item class	41F

**Description****Version:**

Strong base with ground standing surface and dirt trap grooves. Ergonomic and comfortable plastic cap with Santoprene® surface. Flat carbide-tipped scriber for easy marking out even in narrow grooves, exchangeable. Fold-away or removable protection cap for injury-free working. Marking out from 0, drawing dimensions can therefore be transferred directly without the risk of calculation errors. Very easy to read, high-contrast 11 mm-high LCD display. Incl. data output. With fine adjustment and locking screw.

**Standard:**

Strong base with ground standing surface and dirt trap grooves. Ergonomic and comfortable plastic cap with Santoprene® surface. Flat carbide-tipped scriber for easy marking out even in narrow grooves, exchangeable, marking out from 0. Drawing dimensions can therefore be transferred directly without the risk of calculation errors. Fold-away or removable protection cap for injury-free working. With fine setting adjustment and high-speed screw. Very easy to read, high-contrast 11 mm-high LCD display. Incl. data output.

**Function:**

- **Zeroing in any position**
- **Preset**
- **Selectable mm / inches**

- **Data output RS232 Proximity**
- **Hold function**

**Supplied with:**

Scriber No. 444010 size 75.

Battery No. 081560 size CR2032.

**Optional extras:**

Data cable No. 498948.

Calibration: E1

Scale divisions: 0.01 mm

Scale divisions: 0.0005 inch

Error limit: 0.05 mm

Column cross section: 30×12 mm

Base length: 165 mm

Base width: 110 mm

---

**Technical description**

Scale divisions	0.0005 inch
Column cross section	30×12 mm
Scale divisions	0.01 mm
Base width	110 mm
Marking height	600 mm
Base length	165 mm
Error limit	0.05 mm
Number of batteries contained	1
Article no of the battery / rechargeable battery fitted	081560 CR2032
Power supply	Battery-powered
Standard	Manufacturer's standard
Reversible reading	mm / inch
Height of numerals	11 mm
Interface	USB interface
Interface	RS232C interface
Measurement technology	digital
Calibration	E1
Type of product	Height gauge and marking device

---

## Services

Calibration Height gauge / height scriber maximum measuring range 1000 mm	014350 1000
Labelling laser-etched Type	018940

---

## Accessories

Spare scriber, carbide tipped Length 150 mm	444010 150
Button cell / special battery Battery type CR2032	081560 CR2032
Connecting cable Type R2	498948 R2
Connecting cable Type USB2	498948 USB2
Spare scriber, carbide tipped Length 75 mm	444010 75