

**Mitutoyo****Digital height gauge and marking-out system with data output, Marking height: 600 mm****Order data**

Order number	445135 600
GTIN	8010820400005
Item class	44A

**Description****Version:**

Large, high contrast LCD display for easy, error-free reading (character height 10 mm). Rapid and precise adjustment using exact handwheel control. Robust, stable version with solid base and ergonomically shaped handle for effortless handling. Zero / ABS for zeroing in any position (e.g. comparative measurement) or return to absolute scale.

**Supplied with:**

1 battery No. 081560 size 357, 1 carbide tipped scriber No. 443510 size 300 (suitable for both sizes).

**Optional extras:**

Holder No. 445180, data cable No. 497080.

Calibration: E1

Scale divisions: 0.01 mm

Error limit: 0.05 mm

Column cross section: 35×15 mm

Battery life approx.: 2000 h

Base length: 181 mm

Base width: 142 mm

## Technical description

Column cross section	35×15 mm
Marking height	600 mm
Base width	142 mm
Base length	181 mm
Weight	6.4 kg
Error limit	0.05 mm
Scale divisions	0.01 mm
Battery life approx.	2000 h
Number of batteries contained	1
Article no of the battery / rechargeable battery fitted	081560 357
Power supply	Battery-powered
Standard	Manufacturer's standard
Interface	Digimatic interface
Interface	Digimatic interface
Measured value saving	once-off setting of the zero position
Measurement technology	digital
Calibration	E1
Type of product	Height gauge and marking device

## Services

Calibration Height gauge / height scriber maximum measuring range 1000 mm	014350 1000
Labelling laser-etched Type	018940
Calibration Height gauge / height scriber maximum measuring range 1000 mm	024630 1000
600	024640 600

## Accessories

Connecting cable Type USB2	497080 USB2
Connecting cable with data switch Type D1	497100 D1
Connecting cable Type D2	497080 D2
Universal square holding arm	445180
Receiver / USB keyboard interface Type	498965
Button cell / special battery Battery type 357	081560 357
Multi-receiver / USB keyboard interface Type	498975
Connecting cable Type D1	497080 D1
Spare scriber, carbide tipped for marking heights 300 mm	443510 300
Transmitter Type S1	498966 S1
Connecting cable with data switch Type D2	497100 D2
Connecting cable with data switch Type USB2	497100 USB2