

**Digital precision protractor, Beam length: 180 mm****Order data**

Order number	454005 180
GTIN	4045197294661
Item class	46R

Description**Version:**

For easy measurement of angles on components. Can be used with caliper or with digital height gauge. Very easy to fit to caliper - uses only two clamping screws. Can be attached to digital height gauge or marking-out device using square holder.

Supplied with:

Square holder for mounting on height gauges, 2 batteries No. 081561 size LR3.

Calibration: F4

Measuring range: 180 degrees

Reversible reading: 1 minute or 0.01°

Error limit: ±5 arcmin

Length of measuring beam: 35 mm

Weight: 150 g

Technical description

Beam length	180 mm
Reversible reading	1 minute or 0.01°
Error limit	±5 arcmin

Weight	150 g
Length of measuring beam	35 mm
Measuring range	180 degrees
Article no of the battery / rechargeable battery fitted	081560 CR2032
Number of batteries contained	1
Power supply	Battery-powered
Standard	Manufacturer's standard
Measurement technology	digital
Packaging	sturdy box
Calibration	F4
Type of product	Protractor

Services

Calibration Universal protractor	015350
Labelling laser-etched Type	018940
Calibration Universal protractor Type UNI	025710 UNI
UNI	025720 UNI

Accessories

Alkaline-manganese batteries International size LR3	081561 LR3
Alkaline-manganese batteries International size LR3	081556 LR3