



Winkeltronic protractor, resolution 0.1 degrees, Length: 400 mm



Order data

| | |
|--------------|---------------|
| Order number | 467540 400 |
| GTIN | 4016054102320 |
| Item class | 46R |

Description

Version:

Protractor with precise display of the angular position of the movable blade. With integral horizontal and vertical vials. Data storage key for locking the measurement values. Display can be zeroed in any position.

Supplied with:

4 batteries No. 081561 size LR6, case.

Calibration: H2

Measuring range: 0 - 200 degrees

Graduations: 0.1 degrees

Error limit: 0.2 degrees

Technical description

| | |
|-------------------------------|-----------------|
| Graduations | 0.1 degrees |
| Length | 400 mm |
| Measuring range | 0 - 200 degrees |
| Number of batteries contained | 4 |

| | |
|---|---|
| Article no of the battery / rechargeable battery fitted | 081561 LR6 |
| Error limit | 0.2 degrees |
| Power supply | Battery-powered |
| Calibration | H2 |
| Measurement technology | digital |
| Type of product | Spirit level with electronic protractor |

Services

| | |
|--|-------------|
| Calibration Engineer's level / electronic clinometer Accuracy 0,10 mm/m | 016230 0,10 |
| Labelling laser-etched Type | 018940 |
| Calibration Engineer's level / electronic clinometer Accuracy 0,10 mm/m | 026620 0,10 |

Accessories

| | |
|---|------------|
| Alkaline-manganese batteries International size LR6 | 081556 LR6 |
| Alkaline-manganese batteries International size LR6 | 081561 LR6 |