



## Winkeltronic protractor, resolution 0.1 degrees, Length: 600 mm



### Order data

Order number	467540 600
GTIN	4016054325996
Item class	46R

### Description

#### Version:

Protractor with precise display of the angular position of the movable blade. With integral horizontal and vertical vials. Data storage key for locking the measurement values. Display can be zeroed in any position.

#### Supplied with:

4 batteries No. 081561 size LR6, case.

Calibration: H2

Measuring range: 0 - 200 degrees

Graduations: 0.1 degrees

Error limit: 0.2 degrees

### Technical description

Graduations	0.1 degrees
Length	600 mm
Measuring range	0 - 200 degrees
Article no of the battery / rechargeable battery fitted	081561 LR6
Number of batteries contained	4
Error limit	0.2 degrees

Power supply	Battery-powered
Calibration	H2
Measurement technology	digital
Type of product	Spirit level with electronic protractor

### Services

Calibration Engineer's level / electronic clinometer Accuracy 0,10 mm/m	016230 0,10
Labelling laser-etched Type	018940
Calibration Engineer's level / electronic clinometer Accuracy 0,10 mm/m	026620 0,10

### Accessories

Alkaline-manganese batteries International size LR6	081561 LR6
Alkaline-manganese batteries International size LR6	081556 LR6