

STIEFELMAYER

Shaft spirit level, Base Length×Accuracy: 250/2 mm

Order data

| | |
|--------------|---------------|
| Order number | 468800 250/2 |
| GTIN | 4045197207111 |
| Item class | 46R |

Description
Version:

Sturdy housing of high quality special casting; hammer finish. Vee base with ground contact surfaces in the angle (important for marking out, aligning, etc.). All measuring faces are exactly parallel to the axis of the vial. One longitudinal and one transverse vial each of glass. With insulated handles on the housing and protective glass over the vials.

Application:

For aligning surfaces, shafts, machines etc.

Standard:

DIN 877

Accuracy:

1 = with very high sensitivity longitudinal vial **0.02 mm/m.**

2 = with high sensitivity longitudinal vial **0.1 mm/m.**

4 = with normal sensitivity longitudinal vial **0.4 mm/m.**

Calibration: H2

Scale divisions: 0.1 mm/m

Sole width: 40 mm

Technical description

| | |
|-----------------|----------|
| Sole length | 250 mm |
| Scale divisions | 0.1 mm/m |
| Accuracy class | 2 |
| Sole width | 40 mm |

| | |
|-----------------|--------------------|
| Standard | DIN 877 |
| Packaging | sturdy box |
| Calibration | H2 |
| Type of product | Shaft spirit level |

Services

| | |
|--|-------------|
| Calibration Engineer's level / electronic clinometer Accuracy 0,10 mm/m | 016230 0,10 |
| Labelling laser-etched Type | 018940 |
| Calibration Engineer's level / electronic clinometer Accuracy 0,10 mm/m | 026620 0,10 |