

STIEFELMAYER

**Square frame level, Base Length×Accuracy: 150/2 mm**

**Order data**

Order number	469200 150/2
GTIN	4028126004371
Item class	46R

**Description**
**Version:**

Insulated handles on the housing protect against the effects of body heat.

Sturdy frame of high quality special casting; hammer finish. 3 sides Vee ground, 1 side flat. One longitudinal and one transverse vial each of glass. The sensitivity (scale value) of the longitudinal vial is specified on the square.

**Application:**

For aligning horizontal and vertical faces, shafts etc. and for accurate alignment at a 90° angle.

**Standard:**

**DIN 877**

**Accuracy:**

**1** = with very high sensitivity longitudinal vial **0.02 mm/m.**

**2** = with high sensitivity longitudinal vial **0.1 mm/m.**

Calibration: H1

Scale divisions: 0.1 mm/m

Sole width: 37 mm

**Technical description**

Sole length	150 mm
-------------	--------

Accuracy class	2
Scale divisions	0.1 mm/m
Sole width	37 mm
Standard	DIN 877
Packaging	sturdy box
Calibration	H1
Type of product	Square frame level

### Services

Calibration Square frame level Accuracy 0,10 mm/m	016200 0,10
Labelling laser-etched Type	018940
Calibration Square frame level Accuracy 0,10 mm/m	026600 0,10