ALLURIS

Precision hand-held tachometer, Type: CL



Order data

Order number	471300 CL
GTIN	4260244680239
Item class	47F

Description

Version:

Precision hand-held tachometer in **sturdy die-cast aluminium casing.** Large digital display, easy to use. Lengths and speeds in selectable international units. **Laser hand-held tachometer** for non-contact measurements at distances up to 4 m. **Also for contact measurements** using multi-impulse adapter (included).

Application:

Rotational speed measurement: 0.1 – 99999 rpm (mechanically up to 25,000 rpm).

Speed: 0.1 – 3810 m/min

Length measurement: 0.0-99999 m/min

Counting: 0- 99999 Supplied with:

Includes 2 measuring tips, surface disc 6 inch No. 471311, female centre, extension shaft, operating manual, protective case, 2 batteries No. 081561 size LR6. Additionally with screw-in adapter and reflector strips.

Optional extras:

Reflector strips No. 471315.

Calibration: 12

Error limit: 0.006 (±0.5 digit) %

Impulses per revolution (contact measurement): 8 (with adapter)

Measurement distance (for optical measurement): 150 – 1500, maximum 4000 mm

Measurement time: 1 s

Surface disc circumference: 6 inch

Technical description

Measurement distance (for optical measurement)	150 – 1500 , maximum 4000 mm
Impulses per revolution (contact measurement)	8 (with adapter)
Measurement time	1 s
Surface disc circumference	6 inch
Error limit	0.006 (±0.5 digit) %
Number of batteries contained	2
Article no of the battery / rechargeable battery fitted	081561 LR6
Power supply	Battery-powered
Measurement technology	digital
Calibration	12
Type of product	Hand-held tachometer

Services

Labelling laser-etched Type	018940
Calibration Tachometer / stroboscope Type D	027900 D
DAkkS calibration Rotational speed sensor Type D	027910 D

Accessories

Reflector strip set 35 pieces	471315
-------------------------------	--------