

FLUKE.

Voltage and continuity tester, Type: T130**Order data**

Order number	473090 T130
GTIN	095969610506
Item class	47H

Description**Version:**

Two-pole voltage testers with ergonomic one-handed operation for sockets. Measured value display with backlighting. Battery indicator - if the battery is flat the measured voltage can continue to be displayed. Slip-on test prods with wear display. **VDE version**

Function:

IP64: Protected against splashed water from all directions and protected against penetration by dust (dust-tight), also completely protected against touching.

Application:

For professional multi-stage voltage, polarity and continuity testing.

Standard:

HSE GS 38 (Messspitzen); IEC EN 61243-3.

IP Index of Protection: IP 64

Calibration: I1

Display range AC: 6 - 690 V

Display range DC: 6 - 690 V

Display: LED / LCD

Three phase sequence testing: yes

Phase testing: 100V – 690V

Polarity testing: yes

Technical description

FI/RCD protective switch test current	yes
Display	LED / LCD
Display range AC	6 - 690 V
Display range DC	6 - 690 V
Phase testing	100V – 690V
Calibration	I1
Illumination of probe points	yes
Three phase sequence testing	yes
Polarity testing	yes
Continuity testing	visual / acoustic
Overvoltage category	CAT III 690 V
Overvoltage category	CAT IV 600 V
IP Index of Protection	IP 64
Frequency measurement	40 - 400 Hz
Torch function	yes
Number of batteries contained	2
Article no of the battery / rechargeable battery fitted	081551 LR3
Power supply	Battery-powered
Power supply	2× 081561 LR3
Type of product	Two-pole voltage tester

Services

Calibration Voltage tester	017870
----------------------------	--------

Accessories

Alkaline-manganese batteries International size LR3	081556 LR3
Alkaline-manganese batteries International size LR3	081561 LR3

