BENNING

Voltage tester DUSPOL®, Device type: ANALOG

Order data

Order number	473105 ANALOG
GTIN	4014651502611
Item class	47A

Description

Version:
Two-pole voltage tester with VDE kitemark. Shockproof, dustproof body. Protected against sprayed water, with rubberised gripping surfaces.
Function:
IP65: Protected against jets of water from all directions and protected against penetration by dust (dust-tight), also completely protected against touching.
Application:
Suitable for manual crafts, and for working on electrical systems, industrial systems, maintenance, servicing (troubleshooting), For professional multi-stage voltage and polarity testing, **with load switching (30 mA RCB trip by push button).** Approved for voltage testing on **systems up to 1000 V.** Suitable for working on photovoltaic and wind turbine installations and hybrid vehicles.
Standard:
DIN EN 61243-3, VDE 0682-401:2015
IP Index of Protection: IP 65
Calibration: I1
Display range AC: 12 - 1000 V
Display range DC: 12 - 1000 V
Display: plunge coil (illuminated) / LED
Three phase sequence testing: LCD

Phase testing: LCD
Polarity testing: LED

Technical description

Polarity testing	LED
Display	plunge coil (illuminated) / LED
Display range DC	12 - 1000 V
Manufacturer's designation	ANALOG
Three phase sequence testing	LCD
Vibration alarm	yes
Overvoltage category	CAT III 1000 V; CAT IV 600 V
Display range AC	12 - 1000 V
Phase testing	LCD
IP Index of Protection	IP 65
electrical insulation	VDE 1000 V
Calibration	I1
Type of product	Two-pole voltage tester

Services

Calibration Voltage tester	017870

Accessories

Protective case for voltage testers	473111