



## Voltage tester, Type: 750-1



### Order data

Order number	473210 750-1
GTIN	4029547013898
Item class	47B

### Description

**Version:**

Sturdy plastic casing and ergonomic handle shape with non-slip ring for safe working with no risk of slipping. **Clear 360° display** with fibre optic cable.

**Function:**

IP64: Protected against splashed water from all directions and protected against penetration by dust (dust-tight), also completely protected against touching.

**Application:**

For professional multi-stage voltage, continuity, and polarity testing. Suitable for working on electrical systems, industrial systems, maintenance, servicing (troubleshooting),

**Standard:**

**DIN EN 61243-3:2011**

**Supplied with:**

Batteries No. 081561 size LR3, test prod protection and measurement prod extensions.

IP Index of Protection: IP 64

Calibration: I1

Display range AC: 12 - 690 V

Display range DC: 12 - 690 V

Three phase sequence testing: yes

Continuity testing: yes

Overvoltage category: CAT III 1000 V; CAT IV 600 V

Article no of the battery / rechargeable battery fitted: 081551 LR3

## Technical description

Continuity testing	yes
Display range AC	12 - 690 V
IP Index of Protection	IP 64
Three phase sequence testing	yes
Display range DC	12 - 690 V
Overvoltage category	CAT III 1000 V; CAT IV 600 V
Calibration	I1
Number of batteries contained	2
Article no of the battery / rechargeable battery fitted	081551 LR3
Power supply	Battery-powered
Type of product	Two-pole voltage tester

## Services

Calibration Voltage tester	017870
----------------------------	--------

## Accessories

Alkaline-manganese batteries International size LR3	081556 LR3
Alkaline-manganese batteries International size LR3	081561 LR3