



Voltage tester, Type: 750-2



Order data

Order number	473210 750-2
GTIN	4029547013904
Item class	47B

Description

Version:

Sturdy plastic casing and ergonomic handle shape with non-slip ring for safe working with no risk of slipping. **Clear 360° display** with fibre optic cable. **Integral torch** for illuminating the measurement area.

Function:

IP64: Protected against splashed water from all directions and protected against penetration by dust (dust-tight), also completely protected against touching.

Application:

For professional multi-stage voltage, continuity, and polarity testing. Suitable for working on electrical systems, industrial systems, maintenance, servicing (troubleshooting), with load switching (30 mA RCB trip by push button).

Standard:

DIN EN 61243-3:2011

Supplied with:

Batteries No. 081561 size LR3, test prod protection and measurement prod extensions.

IP Index of Protection: IP 64

Calibration: I1

Display range AC: 12 - 690 V

Display range DC: 12 - 690 V

Three phase sequence testing: yes

Phase testing: yes
 Continuity testing: yes
 FI/RCD protective switch test current: yes

Technical description

Display range AC	12 - 690 V
Illumination of probe points	yes
Overvoltage category	CAT III 1000 V; CAT IV 600 V
Three phase sequence testing	yes
Display range DC	12 - 690 V
Phase testing	yes
Continuity testing	yes
IP Index of Protection	IP 64
FI/RCD protective switch test current	yes
Calibration	I1
Number of batteries contained	2
Article no of the battery / rechargeable battery fitted	081551 LR3
Power supply	Battery-powered
Type of product	Two-pole voltage tester

Services

Calibration Voltage tester	017870
----------------------------	--------

Accessories

Alkaline-manganese batteries International size LR3	081556 LR3
Alkaline-manganese batteries International size LR3	081561 LR3