

BENNING**Continuity tester DUTEST pro, Device type: DUTESTPRO****Order data**

Order number	473260 DUTESTPRO
GTIN	4014651501560
Item class	47A

Description**Version:**

High-resistance and low-resistance continuity testing with 3-stage LED display and sound intensity of the test buzzer. External voltage and polarity display, single-pole and contactless phase testing. The buzzer sound intensity (3-stage/OFF) and illumination intensity (4-stage) are adjustable. With high-power LED torch.

Application:

Testing electrical wiring, systems, devices and components.

Standard:

IEC / DIN EN 61010-1, (DIN VDE 0411-1).

Supplied with:

Includes 4 mm test probes, magnetic holder and belt clip.

Optional extras:

Batteries 081561 size LR6.

Display polarity: LED +/-

Display continuity: LED, 3-stage

Continuity testing: 0 – 0.1 / 1 / 10 (LED); 0 – 0.1 (buzzer) k Ω

External voltage display AC / DC: 6 – 400; pulsing warning tone V

single-pole phase test: via 4 mm test lead /non-contact via detector

Article no of the battery / rechargeable battery fitted: 081561 LR6

Technical description

Continuity testing	0 – 0.1 / 1 / 10 (LED); 0 – 0.1 (buzzer) kΩ
Display polarity	LED +/-
Display continuity	LED, 3-stage
External voltage display AC / DC	6 – 400; pulsing warning tone V
Manufacturer's designation	DUTESTPRO
single-pole phase test	via 4 mm test lead / non-contact via detector
Number of batteries contained	3
Article no of the battery / rechargeable battery fitted	081561 LR6
Power supply	Battery-powered
Type of product	Continuity and semiconductor tester

Services

Labelling laser-etched Type	018940
-----------------------------	--------

Accessories

Alkaline-manganese batteries International size LR6	081556 LR6
Alkaline-manganese batteries International size LR6	081561 LR6